



PRODUCT DATA SHEET

DRYLOK® CONCRETE CLEANER & DEGREASER

DESCRIPTION

UGL DRYLOK Cleaner & Degreaser is specially formulated to clean and degrease concrete and masonry surfaces in one easy step, UGL Concrete Cleaner & Degreaser is ideal for cleaning concrete walkways, patios, garage floors, basements, concrete driveways, carports, pool areas, concrete tennis courts, and brick, stucco or concrete walls. Because of its deep cleaning formula, UGL Concrete Cleaner & Degreaser cuts through grease, oil and dirt. Not for use on asphalt or painted surfaces.

SURFACE PREP

UGL DRYLOK Concrete Cleaner & Degreaser should be applied to bare concrete, masonry or stucco. Surfaces to be cleaned must be free of standing water. Sweep or vacuum the surface.

APPLICATION

Wear eye protection and rubber gloves. Apply full strength. Do Not Thin. Pour, brush or spray UGL DRYLOK Concrete Cleaner & Degreaser on the area to be cleaned. Allow cleaner to remain on the surface for 5 minutes, then thoroughly flush with water. For tough stains apply the cleaner & degreaser, let it stand for 5-10 minutes, then scrub with a stiff brush or broom and rinse with water.

Avoid applying in direct sunlight or on excessively hot surfaces. If after cleaning, surface is to be

painted or stained, treat smooth concrete with DRYLOK Etch or muriatic acid, according to manufacturer's directions. A properly etched surface should look and feel slightly rough, like fine sandpaper. If surface remains smooth, repeat the etching procedure until the surface has the proper texture. Thoroughly rinse the surface with clean water.

Note: Allow etching solution to remain on the surface for at least 20 minutes. While etching, the concrete surface should bubble. If some areas do not, this indicates deep oil or grease stains requiring additional cleaning. Scrub these areas again with UGL DRYLOK Concrete Cleaner & Degreaser and repeat the etching procedure. Allow the surface to dry at least 24 hours before staining or painting.

CLEAN-UP

Clean application tools immediately after use with soap and water.

COVERAGE

Depending on the surface porosity, one quart will clean up to 40 square feet.

CAUTION

Contains Petroleum Distillate. Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

FIRST AID

If swallowed, do not induce vomiting. Call a physician immediately. In case of skin or eye contact, flush thoroughly with water. If irritation persists, see a physician.

NOTE

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. KEEP OUT OF REACH OF CHILDREN.

AVAILABILITY

UGL DRYLOK Concrete Cleaner & Degreaser is available in quart and gallon containers. It may be purchased at hardware stores, home centers, paint stores and lumberyards

LR 11/98



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com