



PRODUCT DATA SHEET

DRYLOK® E1 Non-Skid Texture Additive

DESCRIPTION

DRYLOK E1 Non-Skid Texture Additive increases traction and helps prevent slipping and falling by providing a slip resistant coating. Use on garage floors, patios, stairs, basements, driveways, ramps and walkways. For use with DRYLOK E1 1-Part Epoxy Floor Paint and other oil, latex or epoxy floor paints. DRYLOK E1 Non-Skid Texture Additive will not change the drying characteristics or film thickness recommendation of the paint that it is added to.

It will however alter the appearance of the surface by lowering the gloss due to the light scattering effect of the particles that will stick up out of the surface of the paint. DRYLOK E1 Non-Skid Texture Additive contains natural pumice.

PHYSICAL PROPERTIES

% Solids by Weight	100%
% Solids by Volume	100%
Coverage	4oz./Gallon

MIXING

Add 4 oz. bottle to 1 gallon of any oil, latex based or epoxy floor paint. Pour powder into paint and mix thoroughly.

For best results use a drill with a stirring blade. Stir thoroughly before and during application.

CAUTION

Wear goggles to prevent eye irritation. Please read the Material Safety Data Sheet for additional information.

AVAILABILITY

DRYLOK E1 Non-Skid Texture Additive is available in 4 oz. containers. It may be purchased at hardware stores, home Centers, paint stores and lumberyards.

PRODUCT DATA
DRYLOK E1 NON-SKID ADDITIVE

LR 06/10



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com