



# PRODUCT DATA SHEET

## DRYLOK® LATEX BONDING AGENT

### DESCRIPTION

DRYLOK Latex Bonding Agent bonds concrete and plaster to difficult surfaces such as dense or slick concrete, stone, drywall, hardboard and plaster walls. When used as an additive to concrete mixes for patching, DRYLOK Latex Bonding Agent improves the adhesion and increases the resiliency and elasticity of the patch which greatly extends the life of the repaired area. DRYLOK Latex Bonding Agent may also be used to prime plaster cracks by brushing into the crack before filling with plaster. This assures a long lasting, tight bond of the patch to the original surface.

### SURFACE PREP

Surface must be clean, dry and free of oil, grease and powdery or peeling materials. Protect from freezing. If DRYLOK Latex Bonding Agent arrives in a frozen condition, allow to thaw at room temperature for 24 hours before using.

### APPLICATION

Apply by brush or spray. Once DRYLOK Latex Bonding Agent changes from milky color to a clear glaze (approx. 30 minutes) it is dry and ready for a top coating of plaster or concrete.

### MIXING WITH CEMENT POWDER

DRYLOK Latex Bonding Agent can be mixed with concrete patching material in place of water to improve bonding of patch to masonry surfaces. Slowly add DRYLOK Latex Bonding Agent to cement powder (1 quart DRYLOK Latex Bonding Agent to 3 parts cement powder for normal repairs) stirring constantly until consistency is smooth. Adjust consistency if necessary by adding additional latex or cement. When repairing small cracks, mix DRYLOK Latex Bonding Agent and concrete powder to a thin consistency; for deep or wide repairs, use a heavy consistency.

### COVERAGE

Depending on the porosity and texture of the surface, DRYLOK Latex Bonding Agent will cover up to 500 square feet per gallon.

### CLEAN-UP

Application tools should be washed with soap and water immediately after using.

### CAUTION

Keep out of reach of children. Do not take internally.

### TECHNICAL DATA

#### Percent

**Non-Volatile by Weight:** 24.0

#### Percent

**Non-Volatile by Volume:** 21.7

**Weight per gallon:** 8.6

**pH:** 9.3

#### Viscosity:

11 sec. Ford #4 Cup @ 77°F.

### AVAILABILITY

DRYLOK Latex Bonding Agent is available in quart, gallon and 5 gallon containers. These products can be purchased in hardware and paint stores, lumberyards and home centers.

LR 07/07

PRODUCT DATA  
DRYLOK LATEX BONDING AGENT



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com