



PRODUCT DATA SHEET

LATEX BASE DRYLOK® CONCRETE FLOOR PAINT

DESCRIPTION

DRYLOK Concrete Floor Paint is specially formulated to protect and decorate masonry floors in homes and industry, both indoors and outdoors. DRYLOK Concrete Floor Paint is a scientifically formulated "treatment" for masonry floors. It outperforms ordinary floor paint under traffic, washings, weather, acids and alkalis.

SURFACE PREP

Surfaces must be clean and free from dirt, dust, grease, oil, soap, wax and the oily film left by sweeping compounds. Remove all loose or flaking paint by wire brushing or scraping. Dull glossy painted surfaces with UGL D-Gloss Liquid Sander or use sandpaper. On garage floors, DRYLOK Concrete Floor Paint must be applied to bare concrete.

For masonry surfaces subject to heavy use (such as garage floors) highly troweled or extremely smooth concrete, treat with DRYLOK Etch according to directions, before applying DRYLOK Concrete Floor Paint. A properly etched surface should look and feel like fine sandpaper. If surface remains smooth, repeat the etching procedure.

APPLICATION

Stir thoroughly. For unpainted surfaces, first coat should be thinned with one pint of water per gallon. The first coat should be brushed well into the surface. Brush or roller may apply the second coat. For best results, apply two coats. Allow four hours drying time between coats. Paint only when air and surface temperatures are 50°F or higher.

For Garage Floors, allow DRYLOK Concrete Floor Paint to dry five days before subjecting to automobile use.

DRYING

The coating may be subject to light usage after 4 hours, heavy usage after 24 hours. When air and surface temperatures are below 65°F and/or the relative humidity is above 50% the drying time will be extended.

TINTING

Additional shades may be obtained by intermixing DRYLOK Concrete Floor Paint colors or by using Universal tinting colors. Do not use more than 4 fl. oz. of colorant per gallon.

CLEAN-UP

Brushes and rollers clean up easily in warm soapy water.

CAUTION

Avoid prolonged contact with skin or breathing of spray mist. Close container after each use. DO NOT TAKE INTERNALLY KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING

IMPORTANT

NOTE: When using two or more containers of the same color of DRYLOK Concrete Floor Paint, mix together to assure color uniformity.

Floors that are subjected to hydrostatic water pressure (water seeping from underneath the floor) or are continually damp cannot be satisfactorily painted with any paint or coating.

Moisture on basement floors caused by water seeping through masonry walls or through floor-wall joints or cracks must first be eliminated. Use DRYLOK Fast Plug, a quick setting hydraulic cement, to fill floor-wall joints or cracks, and DRYLOK Masonry Waterproofer to seal masonry walls.

Does not exceed maximum VOC 100 g/L.

AVAILABILITY

DRYLOK Latex Concrete Floor Paint is available in quart and gallon cans. The product comes in White, Georgetown Gray, Dover Gray, Persian Red, Gull, Bamboo Beige, Sandstone and Terra Cotta and a dark tint base for custom coloring. It may be purchased at hardware stores, home centers, paint stores and lumberyards.

LR 10/05



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com

PRODUCT DATA
LATEX BASE DRYLOK CONCRETE FL PNT