



PRODUCT DATA SHEET

DRYLOK® MASONRY CRACK FILLER

DESCRIPTION

Drylok Masonry Crack Filler is formulated to seal and waterproof cracks in concrete walks, steps, floors and to replace cracked mortar joints. Fast easy clean up with water. Easy gunning with excellent adhesion, even to damp surfaces.

SURFACE PREP

Opening to be sealed must be free from frost, dust, dirt, oil and loose particles. Hosing and wire brushing facilitate cleaning.

APPLICATION

Place cartridge in any standard caulk gun. Cut end of plastic spout at 45° angle to desired opening size, puncture seal at base of spout. Apply only when air temperature is above 50°F. Force compound tightly into crack. Smooth down with wet putty knife or trowel. May be subjected to traffic in two hours.

COVERAGE

84-87 lineal ft. with 1/8" bead - 48 lineal ft. with 1/4" bead - 18-27 lineal ft. with 3/8" bead

MAINTENANCE

None required. May be painted over immediately with latex paint. Will not bleed.

TECHNICAL DATA

Composition: DRYLOK Masonry Crack Filler is composed of siliconized latex.

% Non-Volatile by Wt. - 83.0

% Non-Volatile by Vol. - 73.8

Wt./Gal. - 13.5 Lbs./Gal.

pH. - 7.5

Viscosity - 700,000 cps. @ 25°C.

LIMITATION

DRYLOK Masonry Crack Filler is non-flammable. It should not, however, be used as a substitute for high temperature furnace cement or fireplace mortar. Deep cracks (over 1/4") should be filled to within 1/4" of top with Oakum before filling with crack filler. Do not store in areas of extreme heat or cold.

CAUTION

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY

AVAILABILITY

DRYLOK Masonry Crack Filler is available in a 10.5 fl. oz. cartridge. It is sold in hardware stores, paint stores, lumber yards and home centers.

PRODUCT DATA
DRYLOK MASONRY CRACK FILLER

LR 2/99



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com