



PRODUCT DATA SHEET

DRYLOK® Natural Look Sealer

DESCRIPTION

DRYLOK Natural Look Sealer is the perfect choice to protect a surface without changing its natural appearance. Natural Look soaks into the surface providing an invisible protective coating. Specially formulated to protect interior and exterior masonry surfaces, including concrete driveways, basement floors, garage floors, concrete sidewalks, patios and terrazzo, brick and slate surfaces.

As A Sealer: DRYLOK Natural Look Sealer penetrates deep to seal and protect masonry against acids, alkalis, road salts, de-icing compounds, household cleaners, gasoline, oil and weathering. Protects against dusting, staining and spalling (surface cracking and pock marking). Treats chalking masonry paint, sandblasted masonry and powdering mortar, before applying a latex paint.

As a Concrete Hardener: When applied to freshly poured concrete, after the surface has set for 24 hours and excess water has been removed, DRYLOK Natural Look Sealer will control water evaporation resulting in maximum concrete hardness.

SURFACE PREP

Remove all dirt, wax, dust, mildew, and loose or scaling material with a scraper, wire brush or stiff bristle brush. Grease, wax and oil should be removed by scrubbing with DRYLOK CONCRETE CLEANER & DEGREASER according to manufacturer's directions or use a heavy duty detergent in warm water. Rinse thoroughly with clean water. Allow to dry. If using a pressure washer, do not use on a pressure setting above

1750 psi to avoid damaging the concrete. Remember, concrete acts like a sponge. Pressure washing and general cleaning may trap residual moisture in the concrete. To check for trapped moisture, tape a 12' x 12" piece of 3 mil plastic or aluminum foil tightly on all four edges to the surface. Remove it after 24 hours. If the floor side of the plastic or foil is damp, allow additional drying and repeat the test. Efflorescence, a white, powdery crystal-like deposit visible on the masonry surface, should be removed with DRYLOK ETCH (liquid or powder) or muriatic acid according to manufacturer's directions. Properly prepared concrete should look and feel like medium grit sandpaper. If concrete remains smooth, repeat etching procedure. Test concrete porosity by sprinkling a few drops of water onto the surface in several areas. If the water is readily absorbed, you are ready to paint. If it beads or lays on the surface, additional cleaning and etching is needed. Rinse thoroughly with clean water and allow to dry for 24 hours. Patch all holes and cracks with DRYLOK CONCRETE PATCH or a suitable cement based patching compound. Be sure to smooth the patch evenly. Allow the patched area to dry thoroughly. NOTE: Rinse etching solutions thoroughly. Etching solutions allowed to dry on masonry surfaces prevent proper curing of the DRYLOK finish coat and may result in the DRYLOK NATURAL LOOK SEALER appearing milky when dry.

APPLICATION

Apply only when air and surface temperature is above 50°F.

DRYLOK Natural Look Sealer appears milky in the can- dries clear. Apply by brush, roller, spray or squeegee. Spread evenly- do not allow puddles or a heavy surface film to occur. Apply one coat using thin even strokes. Extremely porous surfaces may require a second coat. Allow 6 hours drying time between coats.

Do not use on asphalt surfaces. Additional coats will cause surface to be slippery when wet.

On light-colored surfaces, some darkening may take place; test in an inconspicuous area to be sure darkening does not occur. May be applied to surfaces previously coated with a similar treatment.

For best results, test a small area for proper adhesion prior to coating entire surface.

THINNING

Due to variations in porosity, when applied over flagstone, slate, terrazzo or dense, smooth concrete, thin DRYLOK Natural Look Sealer with equal parts of clean, lukewarm water. In addition, light colored concrete may darken unevenly due to variations in porosity. To minimize color variations, thin with water 1 to 1 and test on small area to see final effect.

USED AS A PRIMER

DRYLOK Natural Look Sealer will solidify the surface for painting when applied over powdery surfaces such as chalking masonry paint, sand blasted masonry and powdering mortar. It is also ideal for use as a PRIMER-SEALER under latex, alkyd or polyurethane concrete floor paints or carpeting. For self adhesive floor tiles, check with tile manufacturer for adhesion compatibility.

DRYLOK® Natural Look Sealer

DRYING

Allow 6 hours before subjecting to light foot traffic and 24 hours before subjecting to heavy traffic. During periods of high humidity and/or cool temperatures, allow 24 hours before subjecting to light foot traffic.

AVAILABILITY

DRYLOK Natural Look Sealer is available in gallon and five gallon containers. It is sold in hardware and paint stores, lumberyards and home centers.

COVERAGE

One gallon of DRYLOK Natural Look Sealer will cover up to 400 square feet depending on surface porosity.

CLEAN-UP

Clean tools with soap and water.

MAINTENANCE

None required. Because DRYLOK Natural Look Sealer prevents the penetration of dirt, moisture, etc., coated surfaces are easy to clean.

TECHNICAL DATA

Non-Volatile by Weight - 15.0%
Non-Volatile by Volume - 12.5%
Wt./Gal. - 8.4 lbs.
pH - 8.9
Viscosity - 11 Sec. Ford #4 Cup @ 75°F.
VOC Does not exceed 250 g/L

SPECIFICATION

DRYLOK Natural Look Sealer is not recommended as a waterproofer. For masonry walls subjected to hydrostatic pressure, use DRYLOK Masonry Waterproofing. Do not use over silicone treated surfaces.

