



PRODUCT DATA SHEET

DRYLOK® POURABLE MASONRY CRACK FILLER

DESCRIPTION

DRYLOK Pourable Masonry Crack Filler is formulated to fill and seal cracks on interior and exterior concrete and masonry surfaces. Ideal for sidewalks, walkways, steps, patios, garage floors, etc. Reduces radon gas penetration. Dries to the color of concrete.

SURFACE PREP

Crack to be sealed must be free from frost, dust, dirt, oil and particles. Wire brushing and hosing facilitates cleaning. Remove excess moisture before filling the crack.

APPLICATION

Apply when air and surface temperature are above 50°F (10°C). Do not apply if rain is expected within 24 hours. **SHAKE WELL BEFORE USING.** Use only when cracks are 1/2" wide or less. Cut the tip of the spout to a size slightly smaller than the width of the crack. Squeeze DRYLOK Pourable Masonry Crack Filler tightly into the crack, overfilling slightly to allow for shrinkage.

Deeper cracks should be filled with backer rod or other backing material to within 1/4" of the surface before filling with DRYLOK Pourable Masonry Crack Filler, or apply Crack Filler in 1/4" lifts, waiting 24 hours between applications. Applications under conditions of extreme dampness or high humidity prolongs drying. May be subjected to traffic in 24 hours.

TECHNICAL DATA

% Non-Volatile by Wt. - 85%
% Non-Volatile by Vol. - 72%
Wt./Gal. - 15.40 ± 0.2 lbs/gal
pH. - 7.0 - 9.0
Viscosity - 130 - 135 kus

CAUTION

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. KEEP FROM FREEZING. DO NOT STORE IN AREAS OF EXTREME HEAT OR COLD.

CLEAN-UP

Clean up with water.

AVAILABILITY

DRYLOK Pourable Masonry Crack Filler is available in a 1 quart container. It is sold in hardware stores, paint stores, lumber yards and home centers.

PRODUCT DATA
DRYLOK POURABLE MASONRY CRACK FILLER

LR211



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com