



# PRODUCT DATA SHEET

## DRYLOK® WETLOOK SEALER

### DESCRIPTION

DRYLOK® Wetlook Sealer provides clear weather proof protection against deterioration caused by de-icing salt, gasoline, oil, weathering and water. DRYLOK® Wetlook Sealer seals and builds to a high gloss finish on bare and previously painted masonry surfaces. Ideal for interior and exterior horizontal masonry surfaces, including concrete driveways, garage floors, basement floors, concrete sidewalks, brick walkways, terrazzo and slate surfaces. Can restore beauty and cleanability to a non-glossy latex floor coating.

### SURFACE PREP

Remove all dirt, wax, and dust, mildew, loose or scaling material from the surface with a scraper, wire brush or stiff bristle brush. Grease, wax and oil should be removed by scrubbing with DRYLOK® Concrete Cleaner & Degreaser according to label directions or use a heavy duty detergent in warm water. Rinse thoroughly with clean warm water. Efflorescence (salt deposits) must be removed with DRYLOK® Liquid Etch or muriatic acid according to manufacturer's directions. Rinse thoroughly with clean water.

**IMPORTANT:** Rinse etching solution thoroughly. Etching solution allowed to dry on the masonry surface will prevent proper penetration and curing of the DRYLOK® Wetlook Sealer. Surface must be thoroughly dry. Do not apply to damp surfaces. For exterior surfaces, do not apply if rain is expected within 48 hours. Wait for a dry, rain-free period.

New concrete and freshly applied portland cement based patching compounds must be cured for a minimum of 24 hours prior to application of DRYLOK® Wetlook Sealer.

### APPLICATION

Stir thoroughly before application. DRYLOK® Wetlook Sealer appears

milky in the can but dries clear. Apply only when air and surface temperature is above 50°F and the relative humidity is below 60%. Apply by brush, roller or spray. Spread evenly, do not allow puddles or heavy surface film to occur. Apply at least 2 coats. Multiple coats will be required on highly porous surfaces. Allow overnight drying between coats. As additional coats are applied, gloss build-up will occur and surface will become slippery when wet. **IMPORTANT:** Sealed surfaces and areas adjacent to pools may become slippery when wet. Use caution when walking on surface when moisture is present. **OPTIONAL:** DRYLOK E1 Non-Skid Texture Additive may be added to DRYLOK Wetlook Sealer to improve traction. On light-colored surfaces, some slight darkening may take place.

### APPLICATION OVER EXISTING COATINGS

DRYLOK® Wetlook Sealer may be applied over existing paints and coatings. In addition to normal surface preparation old glossy surface must have the gloss removed by using sandpaper or UGL D-Gloss following label directions. Remove all sanding dust with a vacuum or tack cloth. On many previously coated surfaces only one coat may be required.

### THINNING

Thinning is not normally required but if a high gloss is not desired on sealed or non-porous surfaces like flagstone, slate, terrazzo, dense, smooth or light colored concrete, thin with clean lukewarm water. Test on a small area to see final effect.

### CLEAN-UP

Clean brushes and tools with soap and water. None required.

### MAINTENANCE

None required. Because DRYLOK® Wetlook Sealer prevents penetration of dirt, grease and oil, etc., coated surfaces are easy to clean.

### LIMITATIONS

Not for use over silicone treated surfaces, or on any masonry surface subjected to hydrostatic pressure. Vertical surfaces subjected to hydrostatic pressure should be treated with DRYLOK® Masonry Waterproofing.

### TECHNICAL DATA

**Percent Non-Volatile by Weight:**  
19 to 21%

**Percent Non-Volatile by Volume:**  
17 to 19%

**Weight per gallon:**  
8.5 +/- 0.25 Lbs.

**Flash Point:**  
>212°F

**Viscosity:**  
48 to 52 Ku @ 77°F

**Coverage:**  
400 ft.<sup>2</sup>/Gallon\*

**Recommended Film Thickness:**  
4 wet mils/coat

**VOC:**  
100 g/L

**Dry Time (to touch):**  
1 hour\*\*

**Dry Time (to recoat):**  
4 hours\*\*

**Dry Time (Rain Free):**  
24 hours\*\*

\*Coverage depends upon surface porosity and film thickness applied.

\*\*Dry time may be affected by temperature, humidity and film thickness.

### AVAILABILITY

DRYLOK® Wetlook Sealer comes in 1 gallon containers. It can be purchased in hardware and paint stores, lumberyards and home centers.



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com

PRODUCT DATA  
DRYLOK WETLOOK SEALER