



PRODUCT DATA SHEET

DESIGNER DRYLOK® MASONRY WATERPROOFER

DESCRIPTION

DESIGNER DRYLOK is the most advanced decorative finish in masonry waterproof coatings. DESIGNER DRYLOK imparts beauty and protection in one easy step and its backed by a fully-transferrable 10-year Warranty. Ideal for interior, exterior, above or below grade masonry walls, basement walls, retaining walls, landscape walls, cinder blocks, concrete blocks, stucco and brick. Stops 10 psi, greater than a wall of water 22 feet high. Tested in accordance to ASTM D-7088 Resistance to Hydrostatic Pressure and ASTM D-6904 Resistance to Wind Driven Rain of up to 99 mph.

SURFACE PREP

May be applied on slightly damp surfaces, but best results are obtained when applied over dry surfaces. Wait for a dry (rain-free) period. Surface must be clean and free from dirt, dust, grease, oil, form release compound, frost or paint. Patch all holes or cracks with DRYLOK Fast Plug, or a fast setting hydraulic cement, and smooth the patch evenly with the surface around it. EFFLORESCENCE, a white, powdery, crystal-like deposit visible on the masonry surface must be removed. DRYLOK ETCH (liquid or powder formula) or Muriatic acid, used according to manufacturer's directions, are effective efflorescence removal agents. Re-apply acid until all visible efflorescence is gone. Rinse thoroughly and allow to dry. DESIGNER DRYLOK may be applied over previous coatings in sound condition but the warranty is void. Not formulated for horizontal surfaces subject to foot traffic.

APPLICATION

STIR THOROUGHLY BEFORE AND DURING APPLICATION. DO NOT THIN. Air and surface temperatures must be 50°F, or higher. Apply DESIGNER DRYLOK directly on bare masonry. Apply first coat with a DRYLOK Brush or a good quality nylon bristle brush using a cross hatch (left, right, up, down) technique. Work the DRYLOK into the pores of the masonry, making sure to fill all pores and pinholes (see COVERAGE). Apply two coats. The second coat should be applied using short, smooth strokes to make sure you have an even dispersion of the DESIGNER DRYLOK color flecks.

WARNING

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

IMPORTANT

After applying the second coat of DESIGNER DRYLOK MASONRY WATERPROOFER, carefully inspect the entire wall surface for any pin holes in the waterproof coating. Any affected area should be painted with an additional coat to ensure satisfactory waterproofing results.

GUARANTEED

DESIGNER DRYLOK Masonry Waterproofing, when applied according to directions on a properly prepared bare masonry surface, is warranted to provide a waterproof coating for 10 years from the date of sale or we will refund the cost of the DESIGNER DRYLOK. Warranty includes subsequent owners. This is the exclusive remedy. Excludes leaks due to cracking of the surface, recurring efflorescence, swimming pools and application over surfaces previously coated with a paint other than DRYLOK Masonry Waterproofing.

WARNING

Use only with adequate ventilation. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose and throat irritation. May be harmful if absorbed through skin. Harmful if swallowed. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to dust by wearing an appropriate (NIOSH approved) particulate respirator during sanding. Follow respirator manufacturer's directions for respirator use. Close container after each use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling.

DESIGNER DRYLOK® MASONRY WATERPROOFER

CLEAN-UP

Clean application tools immediately after use in warm, soapy water.

AVAILABILITY

DESIGNER DRYLOK Masonry Waterproofing is available in quart and in one-gallon containers. It may be purchased at hardware stores, home centers, paint stores and lumberyards.

FIRST AID

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. KEEP FROM FREEZING.

For additional health and safety information please refer to the "Material Safety Data Sheet".

DESIGNER DRYLOK Masonry Waterproofing meets all environmental standards for low emissions of solvent vapors.

TECHNICAL DATA

Viscosity 120 to 130Ku
pH 9.0 to 9.9
% Solids by Weight 66 to 68
% Solids by Volume 60 to 63
Coverage up to 60 ft.²/Gallon/Coat
Dry time (to touch)* 1 to 2 hours
Dry time (to recoat)* 3 hours
VOC Content <100 g/L
*Dry time is dependent upon temperature and humidity. Apply when temperature is between 50° and 90° F.

LR 6/11



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com