



PRODUCT DATA SHEET

UGL® 222 LITE SPACKLING PASTE

DESCRIPTION

UGL 222 LITE Spackling Paste is a fast-drying, lightweight compound for interior and exterior use. The product is ideal for patching plaster, drywall, wood, Masonite, masonry and other construction surfaces. For large holes and cracks, UGL 222 LITE smooths on easily, will not shrink, crack or crumble and requires little or no sanding.

SURFACE PREP

Remove all loose dirt, paint, wax, grease and dust. Nail heads and other metal surfaces should be primed with a metal primer. UGL 222 LITE and surface temperature of area to be patched must be above 50°F.

All exterior applications must be painted.

APPLICATION

Stir and apply with a putty knife. Push UGL 222 LITE firmly into hole or crack, smoothing the material with long strokes of the putty knife. For extra-smooth finish, lightly smooth patched area with a wet putty knife.

PAINTING

UGL 222 LITE can be painted almost immediately with latex paint. Before applying an oil-based paint, allow material to dry thoroughly. For best results, prime patched areas. Allow these areas to dry thoroughly before sanding.

CLEAN-UP

Clean tools and spills with soap and water.

TECHNICAL DATA

Percent non-volatile by weight: 43.8
Percent non-volatile by volume: 72.3
Weight per gallon: 4 lbs.
pH: 5.7
Viscosity: Stiff paste

AVAILABILITY

UGL 222 LITE Spackling Paste is available half-pint, pint, quart and gallon containers. It is sold in hardware and paint stores, home centers, paint stores and lumberyards.

PRODUCT DATA
UGL 222 LITE SPACKLING PASTE

