



PRODUCT DATA SHEET

UGL® 222 SPACKLING PASTE

DESCRIPTION

UGL 222 Spackling Paste is an all-purpose surfacing compound for interior and exterior use. The product is ideal for patching cracked plaster, filling nail holes, repairing wall tile and smoothing surface imperfections on unprimed wood. UGL 222 Spackling Paste saves time-no mixing, no waste it builds up without sagging and sands easily.

SURFACE PREP

Remove all loose dirt and scaly or powdery material. All metal, including nail heads, should be primed with a metal primer. UGL 222 Spackling Paste and surface temperature of area to be patched must be above 50°F. All exterior applications must be painted.

APPLICATION

Apply with a putty knife or broad knife. Deep cracks should be filled in two steps, allowing the material to dry thoroughly between applications. To patch sand-finish plaster, add white sand to match the texture of the adjoining area.

PAINTING

UGL 222 Spackling Paste can be painted over immediately after drying with any type of decorative finish.

CLEAN-UP

Clean tools with water.

TECHNICAL DATA

Percent non-volatile by weight: 69.82
Percent non-volatile by volume: 50.44
Weight per gallon: 13.2 lbs.
pH: 8+
Viscosity: Stiff paste

AVAILABILITY

UGL 222 Spackling Paste is available half-pint, pint, quart and gallon containers. It is sold in hardware and paint stores, home centers, paint stores and lumberyards.

CAUTION

Prolonged contact with skin during mixing or application may cause irritation some cases. If splashed on skin or in eyes, flush thoroughly with water. Do Not Take Internally, Avoid Breathing Dust. Keep Out of The Reach of Children.

PRODUCT DATA
UGL 222 SPACKLING PASTE

