



PRODUCT DATA SHEET

50-Year LASTICAULK® ACRYLIC LATEX CAULK WITH SILICONE

DESCRIPTION

UGL 50-Year Lasticaulk is a non-staining, paintable acrylic latex-silicone compound designed for superior adhesion and longer life. Lasticaulk guns easily and forms a durable, elastic, watertight seal that resists weather and mildew. Lasticaulk helps protect your home against drafts and moisture. It bonds perfectly to wood, masonry, metal, tile or glass.

The product can be used on interior or exterior surfaces such as around windows, doors, siding, sills, thresholds, eaves, soffits, gutters, downspouts, flashings, air conditioners, vents, porches, decks, countertops and gas pipe and plumbing entrances and exits. Will not affect painted surfaces. (Not recommended for marine use or on areas below water level or grade level.)

SURFACE PREP

Opening to be sealed (up to 1/2-inch by 1/4-inch wide) must be free from moisture, mildew, frost, dirt, rust and loose caulk, putty or mortar. Deep cracks (over 1/4-inch) should be filled to within 1/4-inch of surface with a backing material such as oakum prior to caulking. Place cartridge in any standard caulk gun. Select size of bead by cutting plastic spout at number indicated (5/16, 1/4 or 1/8 inch) on the cartridge's tip. Cut spout at 45-degree angle.

APPLICATION

Angle spout tip over space to be filled. Start at bottom of crack and work up as void is filled. The caulk bead may be easily smoothed with wet finger or cloth. Before curing, remove excess caulk with damp cloth. Lasticaulk can be painted over immediately with latex paint. Allow compound to dry overnight before applying an oil based paint. The drying and curing of all latex caulks (normally cured in 12 hours) is affected by temperatures and humidity. Apply only when air and surface temperatures are above 50°F (10°C). Application under conditions of extreme dampness or high humidity prolongs drying and curing time by as much as 36 hours, rendering caulk vulnerable to driving rain.

25 YEAR WARRANTY

Use contents of cartridge as directed within one year from date of purchase. If this material fails within 25 years of application, UGL will replace an equal amount of material free of charge. Return cartridge and proof of purchase to UGL. Liability is limited to replacement of product. This warranty applies to residential use only.

COVERAGE

36 Linear feet with 1/4-inch bead.

LIMITATIONS

Not for use as an expansion joint sealant, or on areas below water level.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF
CHILDREN.**

TECHNICAL DATA

WHITE, ALMOND, BROWN & GRAY

Percent Non-volatile by weight
- 80.0%

Percent Non-volatile by volume
- 69.0%

Weight per gallon: 12.94 pounds per gallon

pH - 7.8

Viscosity - 325 @ 77°F

ASTM Spec. C-834-76

CLEAR

Percent Non-volatile by weight
- 58.0%

Percent Non-volatile by volume
- 55.5%

Weight per gallon: 8.8 pounds per gallon

pH - 9.0

Viscosity - 325 @ 77°F

ASTM Spec. C-834-76

AVAILABILITY

UGL 50-Year Lasticaulk comes in a 10.5 fl. oz. (310 ml.) caulking cartridge and is available in white, clear, almond, brown and gray. It may be purchased in hardware stores, home centers, paint stores and lumberyards.

LR 9/01

PRODUCT DATA
50-Year LASTICAULK



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com