



PRODUCT DATA SHEET

D-GLOSS® WATER-BASED LIQUID SANDER & CLEANER

DESCRIPTION

UGL Professional Strength Water-Based D-Gloss Liquid Sander & Cleaner prepares surfaces for recoating. Removes surface contaminants and provides a slight "etching" of the surface allowing subsequent coatings to bond. Dulls paint, enamel, varnish and polyurethane. For interior or exterior surfaces. Environmentally friendly, nonflammable, non-caustic, and virtually odor free.

APPLICATION

For your safety wear neoprene gloves and eye protection with side shields. Always test for compatibility in an inconspicuous area before recoating the prepared surface. Apply D-Gloss liberally by spraying the area to be prepared. In order to achieve a deep cleaning and a light "etch" or to remove the slippery feel of the coated surface, allow D-Gloss to sit on the surface for 1-5 minutes for Latex Base Paint, 5-15 minutes for oil-based paints and polyurethane coatings. After the D-Gloss has had sufficient contact time, wipe with a clean cloth or nonabrasive pad. Fold and change cleaning area on cloth to prevent re-depositing of soils. NOTE: Several applications may be required depending on the age and condition of the surface to be prepared. In addition, kitchen areas with grease deposits may require cleaning with a grease cutting detergent. Allow surface to dry 1-15 minutes before applying new finish. Apply new finish within 1 hour to achieve maximum bonding of the top-coat.

CAUTION

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead.

CLEAN UP

Soap and Water

CAUTIONS

May cause eye or skin irritation. Harmful if swallowed. Use only with adequate ventilation. Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Keep container tightly closed, when not in use. Wash thoroughly after handling.

FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If affected by inhalation of vapor, remove to fresh air. If swallowed, do not induce vomiting, get medical attention in case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

KEEP OUT OF REACH OF CHILDREN AND PETS. PROTECT FROM FREEZING. DO NOT TAKE INTERNALLY.

DOES NOT EXCEED MAXIMUM VOC 28%

AVAILABILITY

D-Gloss Water-Based Liquid Sander and Cleaner is available in quart plastic spray bottle. It may be purchased in hardware stores, home centers, paint stores and lumberyards.

LR 01/08



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com

PRODUCT DATA
D-GLOSS WATER-BASED LIQUID SANDER & CLEANER