



PRODUCT DATA SHEET

UGL® DRIVEWAY CRACK FILLER

DESCRIPTION

UGL Driveway Crack Filler seals and waterproofs cracks in asphalt driveways, sidewalks, parking lots and recreation areas. Driveway Crack Filler is non-flammable, guns easily, does not bleed and adheres excellently to damp surfaces. Fast, easy clean-up with water.

SURFACE PREP

Opening to be sealed must be free from moisture, frost, dirt, dust and loose particles. Deep cracks (over 1/4-inch) should be filled to within 1/4-inch of the surface with a backing material such as oakum prior to sealing. Use only in cracks 1/2-inch wide or less. Hosing and wire brushing facilitates cleaning. Remove excess moisture and ponded water with brush or dry cloth before sealing.

APPLICATION

Place cartridge in any standard style caulk gun. Select the size of the bead by cutting the plastic spout at the number indicated (5/16, 1/4) on the cartridge tip. Cut spout at a 45-degree angle. Puncture inner seal in spout with screwdriver. Force compound tightly into the crack. Smooth down patch with a wet putty knife or trowel. Surface may be subjected to traffic in two hours. Allow Driveway Crack Filler to dry overnight before painting with an asphalt base paint. The drying and curing of all latex sealants (normally cured in 12 hours) is affected by temperature and humidity. Apply only when air and surface temperatures are above 50°F (10°C). Application under conditions of extreme dampness or high humidity prolongs drying and curing time by as much as 36 hours, rendering sealant vulnerable to driving rain. Clean tools with soap and water upon completion. Do Not Store In Areas of Extreme Heat or Cold. Keep From Freezing.

CAUTION - DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

TECHNICAL DATA

% Non-Volatile by Weight: 82.8%
% Non-Volatile by Volume: 71.3%
Density - 13.6 pounds per gallon
Consistency: Soft Paste
Coverage: 36 lineal feet with 1/4-inch bead

AVAILABILITY

UGL Driveway Crack Filler is available in black in a 10.5 fluid ounce (310ml) caulking cartridge. It may be purchased in hardware stores, home centers, paint stores and lumberyards.

PRODUCT DATA
UGL DRIVEWAY CRACK FILLER



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com