



PRODUCT DATA SHEET

FASTRIP® PAINT AND VARNISH REMOVER

DESCRIPTION

UGL Professional Strength FASTRIP Paint and Varnish Remover. This environmentally friendly, nonflammable stripper is ideal for the removal of all types of paints, polyurethanes and marine grade finishes.

Semi-paste formula is perfect for horizontal and vertical surfaces.

APPLICATION

For your safety wear neoprene gloves and eye protection with side shields. On surfaces other than wood, metal, glass or masonry, test for compatibility in an inconspicuous area.

Apply FASTRIP liberally to the area(s) to be stripped-do not brush out. Let finish soften until the bare surface can be exposed by gentle scraping. Don't rush-let FASTRIP Paint and Varnish Remover do the work. Avoid application in direct sunlight. Check the coating every 15 minutes for ease of removal by gently scraping the surface. Several applications may be necessary depending on the thickness and the age of the coating to be removed. If a second application is required, apply over the first coat. On rounded or uneven surfaces the use of an old toothbrush simplifies the removal process.

Allow FASTRIP to sit on the surface 15-20 minutes for latex or oil based paints. For polyurethane coatings allow from 15 minutes - 2 hours depending on the type of polyurethane.

When the remover has completely penetrated the coating, remove completely with a scraper or nonabrasive pad.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC.

EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop.

Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP

Soap and Water

CAUTIONS

May cause eye or skin irritation. Harmful if swallowed. Use only with adequate ventilation. Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Keep container tightly closed, when not in use. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN AND PETS. PROTECT FROM FREEZING. DO NOT TAKE INTERNALLY. DOES NOT EXCEED MAXIMUM VOC 50%

FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If affected by inhalation of vapor, remove to fresh air. If swallowed, do not induce vomiting, get medical attention immediately. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

AVAILABILITY

Available in quarts and half-gallons plastic jugs. It may be purchased in hardware stores, home centers, paint stores and lumberyards.

PRODUCT DATA
FASTRIP PAINT AND VARNISH REMOVER

LR 1/10



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com