



# PRODUCT DATA SHEET

## GLAZOL® ELASTIC GLAZING COMPOUND

### DESCRIPTION

Superior to putty, Glazol may be used for glazing wood or metal sash, setting plumbing fixtures and filling cracks and nail holes. Glazol remains pliable, does not chip or crack and has year-round workability. Glazol forms a "cushion" against shock and vibration when used in replacing broken glass and is ideal for use as a knife-grade compound.

### SURFACE PREP

Remove old putty and make sure surface is clean and dry. Air and surface temperature should be above 40°F. For best results, window frames should be primed with a good oil-base primer. For bedding glass, if desired, soften Glazol slightly with a small amount of mineral spirits. When installing glass into frame, secure with glaziers points or clips.

### APPLICATION

Glazol is ready to use. Place Glazol in hands and roll to warm and soften. Apply with putty knife using flat side of blade against material, not the bottom edge. Press Glazol onto sash, filling height and width of L-shaped recess completely. Smooth to an angle that sheds rain. For best results, Glazol should be painted after it is applied. When used under latex paint, allow Glazol to cure for several days before painting. Before painting with oil-based paint, allow Glazol to dry overnight.

### IMPORTANT

Glazol is not for use on insulated glass units with an organic seal, plastic window panes, or any window pane over 48" in any direction. To minimize skinning of unused material, cover with aluminum foil or plastic wrap before replacing lid.

### CLEAN-UP

Before setting, excess material may be removed with mineral spirits. After setting, material must be cut or scraped away. Clean tools with UGL Fastrip Brush Cleaner or mineral spirits.

### CAUTION

To avoid spontaneous combustion during temporary storage, soak soiled rags and wastes immediately after use in a water-filled closed metal container. Do not take internally. Close container after each use. **KEEP OUT OF THE REACH OF CHILDREN**

### AVAILABILITY

UGL Glazol Elastic Glazing Compound is available in half-pint, pint, quart and gallon containers. Glazol is sold in hardware stores, home centers, paint stores and lumberyards.

PRODUCT DATA  
GLAZOL ELASTIC GLAZING COMPOUND

LR 2/99



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com