



PRODUCT DATA SHEET

UGL® MEX®

DESCRIPTION

MEX by UGL is a phosphate-free cleaning powder for use in the home, garage or workshop. It mixes with water to any desired strength. MEX is excellent for removing shellac, grease, wax, dirt and soot from masonry, wood floors, patios, grills, plumbing fixtures, appliances, etc. It also cleans soot and smoke stains from brick and stone fireplaces and hearths.

PREPARATION

STRONG SOLUTION

Removes shellac and built-up wax from wood floors and removes grease and oil from garage floors, driveways, concrete walls, etc. Dissolve one cup of MEX in one gallon of hot water. Apply hot solution liberally with a brush or mop. Use a stiff brush to loosen finish. Remove residue, rinse with clean, hot water and wipe dry. Wipe up spills from wood surfaces to prevent spotting or staining.

MODERATE SOLUTION

For floors: wood, linoleum, vinyl, rubber, asphalt, ceramic and patios. Dissolve 1/2 cup of MEX in one gallon of hot water. Use damp mop, sponge or cloth to wipe up dirt. Rinse with clean, hot water. Wipe up spills from wood surfaces to prevent spotting or staining. Scrub grills, pots, pans, garbage pails, greasy equipment or machines with stiff brush. Rinse with hot water.

MILD SOLUTION

For general cleaning of floors, walls, woodwork, sinks, tubs, tile, refrigerators, washers, etc. Dissolve 1/4 cup of MEX in hot water. Use damp sponge or cloth. When washing walls, work from bottom up.

Clean small areas at a time. Rinse with clean, hot water and wipe dry. Note: If solution of MEX or rinse water is allowed to stand too long on certain open-grain woods, staining may take place. To lighten, treat with 5% solution of oxalic acid in water. Rinse thoroughly and wipe dry.

CONTAINS

Sodium metasilicate, sodium sesquicarbonate, sodium perborate and sodium carbonate.

CAUTION

Do not breathe dust. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Wear rubber gloves and eye protection. In case of skin or eye contact immediately flush eyes and skin with plenty of water for at least fifteen (15) minutes and get medical attention. If inhaled, remove to fresh air, get medical attention. If swallowed, do not induce vomiting. Give large quantities of water if conscious. Get medical attention immediately. Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

PRODUCT DATA
UGL MEX

LR 10/10



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com