



PRODUCT DATA SHEET

UGL® PLASTER OF PARIS

DESCRIPTION

UGL Plaster of Paris is specially formulated for use in setting marble, replacing tile, making moldings, castings. Plaster of Paris sets with extreme hardness and strength. It will not dust or powder after drying regardless of how thinly it is applied. Plaster of Paris is highly adhesive, dries pure white and can be sanded to a smooth finish.

PREPARATION

Remove dust, scaling paint and loose plaster before applying Plaster of Paris.

APPLICATION

Depending on the project, Plaster of Paris can be applied with a putty knife, trowel or with your hands. When applying with hands, rubber gloves must be worn. If the surface is made of an absorbent material, it should be dampened with water before Plaster of Paris is applied.

SETTING TIME

Setting time of Plaster Paris varies from 25 minutes to one hour, depending on thickness. Allow Plaster of Paris to dry properly before sanding or applying primers. When Plaster of Paris becomes completely and uniformly white and hard, it can be sanded to a smooth finish.

CLEAN UP

Clean tools with soap and water upon completion.

CAUTION

This product contains Calcium Sulfate Alpha-Hemihydrate. When mixed with water this material hardens and then slowly becomes hot. DO NOT attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissues. When mixing or dry sanding, dust may cause irritation to eyes, nose, throat or upper respiratory system.

Close container after each use. Avoid exposure to dust by wearing an appropriate NIOSH approved particulate respirator. Avoid contact with eyes and skin. When using wear impermeable protective gloves. Wear goggles or protective glasses with side shields. Do not ingest.

First Aid: In case of contact, immediately flush eye or skin with plenty of water for at least 15 minutes. If affected by inhalation, move to fresh air. If swallowed, get medical attention immediately.

Keep out of reach of children.

TECHNICAL DATA

% Non-Volatile by Wt. - 100
% Non-Volatile by Vol. - 100
Density - 2.9 pounds per Cubic Foot

AVAILABILITY

UGL Plaster of Paris is available in white in a 4 pound plastic pail. It may be purchased in hardware stores, home centers, paint stores and lumberyards.

PRODUCT DATA
UGL PLASTER OF PARIS

LR 6/07



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com