



PRODUCT DATA SHEET

UGL® PLASTER PATCH

DESCRIPTION

Plaster Patch is the original pure white, slow setting, glue base marble patching plaster. Plaster Patch can easily be troweled to a featheredge. Its greater plasticity prevents it from crumbling and rolling under the trowel. It is more adhesive because of its glue base.

PREPARATION

Remove all broken or loose plaster around area to be patched. Dampen the entire area including plaster and wooden laths with clean water.

MIXING: Add 3 1/4 cups of Plaster Patch to 1 cup clean water in a clean container. Using a mixing paddle, stir thoroughly to form a stiff paste. Small amounts of Plaster Patch can be added to adjust consistency. Stir slowly and long enough to obtain the desired consistency. Prolonged mixing will speed up the set time.

IMPORTANT: Clean out all Plaster Patch that has set before remixing a new batch in the same container. If old mix which as set, is not removed from the container a chemical reaction will take place, causing the new batch to set much faster.

APPLICATION

Apply with a trowel or putty knife. Force the Plaster Patch into the area. Smooth out the patch with the surrounding surface and allow patch to dry. After area has completely dried, sand patch smooth using fine sandpaper. For best results, spot prime before painting.

Setting time of Plaster Patch is approximately 1½ hours. Clean application tools immediately after use with warm, soapy water.

NOTE

Plaster Patch is specially formulated for repairing large defects in plaster walls. When smoothing wall surfaces or repairing fine cracks, small breaks and scratches in wood, wall board, plaster or masonry, use UGL 222 or 222 Lite Spackling Paste.

CAUTION

CONTAINS: Calcium Sulfate Alpha-Hemihydrate. When mixed with water this material hardens and then slowly becomes hot. **DO NOT** attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissues. When mixing or dry sanding, dust may cause irritation to eyes, nose throat or upper respiratory system.

Close container after each use. Avoid exposure to dust by wearing an appropriate NIOSH approved particulate respirator. Avoid with eyes and skin. When using, wear impermeable protective gloves, Wear goggles or protective glasses with side shields. Do not ingest.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. If affected by inhalation, move to fresh air. If swallowed, get medical attention immediately. **KEEP OUT OF THE REACH OF CHILDREN.**

TECHNICAL DATA

Percent Non-Volatile by Weight: 100%

Percent Non-Volatile by Volume: 100%

Density - 2.7 pounds per Cubic Feet

AVAILABILITY

UGL Plaster Patch is available in a 4 pound plastic pail. It may be purchased in hardware stores, home centers, paint stores and lumber yards.

PRODUCT DATA
UGL PLASTER PATCH

LR 6/07



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com