



PRODUCT DATA SHEET

UGL® RAIZOFF PAINT REMOVER

DESCRIPTION

UGL Raizoff Paint Remover removes all conventional finishes quickly and efficiently. The “penetrating performance” of Raizoff leads all others in its field. Excellent for removing paint, enamel, lacquer, varnish and shellac. Raizoff will not stain or raise the grain of the wood, nor harm plaster, metal, glass or nylon bristle brushes. Raizoff contains no acids or caustics.

PREPARATION

Have area well ventilated where Raizoff is to be used. Remove cap with caution to release possible pressure. Replace cap and shake well before using.

APPLICATION

Brush on in one direction-do not brush out. Let finish soften until bare surface can be exposed by gentle scraping. Do not rush-let Raizoff do the work. If a second coat is required, apply it over the first coat. Remove dissolved finish with steel wool or scraper. On rounded or uneven surfaces, the use of an old tooth brush simplifies the removal.

No special after wash is necessary. Allow surface to dry thoroughly before applying new finish.

Follow manufacturer’s directions while refinishing.

Do not permit Raizoff to come into contact with linoleum, asphalt, rubber, tile or plastics.

CAUTION

Extremely Flammable. Do not use near fire or flame. Use only in a well-ventilated area. Contact with flame or hot surfaces may produce toxic gases. Do not store near heat or display in windows. Open container carefully and close after each use. Do not transfer contents to unlabeled containers. Keep out of reach of children.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area.

This product contains a chemical known to the state of California to cause cancer, reproductive or developmental toxicity.

FIRST AID

If swallowed : Give one or two glasses of water. Call physician, hospital emergency room, or poison control center immediately for instructions to induce vomiting. When medical advice is not available, induce vomiting using syrup of Ipecac, according to directions. If Ipecac is unavailable, induce vomiting with finger or back of spoon. Get prompt medical attention.

In case of contact with eyes, flush with water for 15 minutes. Get prompt medical attention. In case of contact with skin, wash thoroughly.

TECHNICAL DATA

Weight: 6.88 lbs/gal
Contains Methanol, Acetone and Toluene. **Cannot be made non-poisonous.**

Contains no Methylene Chloride.

AVAILABILITY

UGL Raizoff Paint Remover is available in pint, quart and gallon cans. Raizoff may be purchased in hardware stores, home centers, paint stores and lumber yards.

PRODUCT DATA
UGL RAIZOFF PAINT REMOVER

LR 3/02



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com