



PRODUCT DATA SHEET

READY MIXED TILE GROUT

DESCRIPTION

UGL Ready Mixed Tile Grout and Repair Cement is an acrylic latex formulation with silicone for use with ceramic and mosaic tile. It can be used straight from the can to grout new tile, regrout old tile and reset tile and fixtures. The product is stain and mildew resistant and may be subjected to water after 24 hours.

APPLICATION

Old Work

Using a sharp tool like an awl or grout saw, remove old grout from joint, clean with a liquid detergent and rinse thoroughly. For easy application, make sure area is damp. Apply grout with sponge, putty knife or hand (wear rubber or latex gloves), working grout well into joints.

After 30-40 minutes set time, wipe off excess with a damp cloth, squeegee or sponge, wiping diagonally across tiles. When grout is firm (in about one hour), polish surface with clean, dry cloth.

New Work

Using a clean wet sponge or cloth, clean surface and dampen joints by wiping tile vertically and horizontally. Wipe off excess water with a cloth, leaving surface damp. Apply grout as described above. Clean tools with water immediately after use.

TINTING

May be tinted to light shades with universal tinting colors. Use only 10 percent of color normally recommended and thoroughly blend in color using a paint shaker.

NOTE

On shower floors and other tiled surfaces subject to standing water, use UGL Powder Tile Grout.

CAUTION

Do not take internally. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN.

PRODUCT CHARACTERISTICS
AVAILABILITY

TECHNICAL DATA

Percent Non-Volatile by Weight
– 80.1%

Percent Non-Volatile by Volume
– 64.3%

Viscosity: Soft paste

Density – 15.24 pounds per gallon

AVAILABILITY

UGL Ready Mixed Tile Grout is available in wide mouth ½-pint, pint and quart containers. It is sold in hardware stores, home centers, paint stores and lumberyards.

PRODUCT DATA
READY MIXED TILE GROUT

