



PRODUCT DATA SHEET

UGL® SAFE GRIP® CONTACT CEMENT

DESCRIPTION

UGL Safe Grip Contact Cement is a fast drying, instant, nonflammable adhesive. Safe Grip is waterproof, needs no clamps, resists oxidation and is heat resistant. It is ideal for use on metal, china, linoleum, rubber, fabric, leather, plastics and high pressure laminates.

SURFACE PREP

Surface to be bonded must be clean, dry, and free from oil, wax, paint, varnish or other finishes. The temperatures of the Safe Grip Contact Cement, the surface to be bonded and air temperatures should be at least 50°F.

APPLICATION

Apply in one direction only, not back and forth. A uniform glossy film shows the surface has been covered properly. One coat is generally sufficient except on porous surfaces. Contact of parts to be bonded should be made within 30-40 minutes after applying cement.

IMPORTANT

Solvents may cause softening of some plastics such as polystyrene. Before using, try Safe Grip Contact Cement on an unused piece of material or in an inconspicuous place to test compatibility with the surface. Naphtha or mineral spirits are recommended for removal of Safe Grip from equipment and surfaces on which it has been spilled.

CAUTION

Use this product outdoors if possible. If you must use it indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. Do not use in basement or other unventilated areas. If properly used, a respirator may offer additional protection. Obtain professional advice before using a respirator. A dust mask does not provide protection against vapors.

Open container carefully and close after each use. Clean up waste, paper, and rags promptly and dispose of in metal container after solvent has evaporated.

Contact with flame or hot surfaces may produce toxic gasses. Harmful or fatal if swallowed.

This product contains Methylene Chloride, which as been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

This product contains a chemical known to the state of California to cause cancer, reproductive or developmental toxicity.

KEEP OUT OF THE REACH OF CHILDREN.

FIRST AID

If swallowed, immediately give one or two glasses of water and call a physician, hospital emergency room or poison control center. In case of eye contact, immediately flush

with water and call physician. In case of contact with skin, wash thoroughly.

COVERAGE

One pint will cover approximately 22-35 square feet.

TECHNICAL DATA

Contains Methylene Chloride; 1,1,1 - Trichloroethane and Toluene.
Percent Non-Volatile by Weight – 30.6%
Percent Non-Volatile by Volume – 34.1%
Viscosity - 100 + 4 KU @ 77°F
Density – 9.21 pounds per gallon.

AVAILABILITY

UGL Safe Grip Contact Cement is available in pint, quart and gallon containers. It may be purchased in hardware stores, home centers, paint stores and lumberyards..

LR 6/99

PRODUCT DATA
UGL SAFE GRIP CONTACT CEMENT



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com