



# PRODUCT DATA SHEET

## TEMPROOF® 1200°F BBQ GRILL AND STOVE PAINT

### DESCRIPTION

UGL Temproof 1200°F BBQ Grill and Stove Paint resists peeling and blistering under high heat conditions and remains black at temperatures up to 1200 °F. Use it to restore the finish on steel or cast iron stoves, outdoor grills and other metal surfaces, both indoors and out, wherever a high quality, flat-black finish is desired.

### SURFACE PREP

Apply only to clean, dry surface at room temperature (65° - 85°F). Do not apply to a hot surface. Be sure all pilot lights or other sources of ignition are turned off. Remove all oil, dirt, wax, polish or grease with a suitable solvent. Remove rust or glossy paint with fine sandpaper.

### APPLICATION

Stir Temproof 1200°F BBQ Grill and Stove Paint thoroughly before and during application. Apply with a high quality brush, using smooth even strokes. Maintain a wet surface edge to prevent lap marks. Allow to dry two to four hours before applying a second coat. One coat is usually sufficient for interior use. For exterior use, two coats should be applied for maximum durability. If you wish to apply paint by spraying, thin with mineral spirits or paint thinner at the rate of one quart of thinner per gallon of paint. Allow stove to dry 24 hours before applying heat. During the first firing after painting, be sure to maintain proper ventilation.

### COVERAGE

25-35 square feet per pint, depending on surface.

### CLEAN-UP

Clean tools and brushes with UGL® Fastrip® Brush Cleaner or mineral spirits. To avoid spontaneous combustion during temporary storage, soak soiled rags and wastes immediately after use in a waterfilled closed metal container.

### CAUTION

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Petroleum Distillate. Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent), or leave the area. **KEEP OUT OF REACH OF CHILDREN.** If swallowed, do not induce vomiting. Call physician immediately. Use with adequate ventilation.

### TECHNICAL DATA

Percent Non-Volatile by Weight: 34.0  
Percent Non-Volatile by Volume: 20.0  
Viscosity: 50-55 KU @ 25°C  
Weight per gallon: 7.83 lbs./gal.  
VOC: less than 650 g/l  
VOS: less than 5.4 lbs./gal.

### AVAILABILITY

TEMPROOF 1200°F STOVE PAINT is available in pints and 11-ounce spray cans. It is sold in hardware and paint stores, home centers, stove specialty stores and lumber-yards.

LR 04/02



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com

PRODUCT DATA  
TEMPROOF 1200°F BBQ GRILL & STOVE PNT