



PRODUCT DATA SHEET

UGL® POWDER TILE GROUT

DESCRIPTION

UGL Powder Tile Grout repairs and restores bathroom, kitchen, and wall tile to its original beauty. Fills cracks around sink and bathtub wall tile and ceramic fixtures. Seals seams between floor and wall tile.

SURFACE PREP

Surface must be clean. Remove soap film by wiping with denatured alcohol. Remove mildew with a bleach and water solution.
NEW WORK: Mastic adhesive must be fully cured. Surface must be clean and firm.
OLD WORK: Remove all old and loose grout. Clean surface thoroughly. Replace damage tile.

MIXING

Mix UGL Tile Grout at a ratio of 2 1/2 cups Tile Grout to 1 cup clean water in a clean container. Slowly add water, stirring constantly until a heavy, creamy consistency is obtained. Do not mix more than can be used in 45 minutes.

APPLICATION

Dampen entire surface using a clean, wet sponge. This will ensure proper cure of Tile Grout. To avoid skin irritation, wear rubber gloves. Force Tile Grout into crack or joint with a plastic putty knife. Smooth the area while damp and allow 30 minutes for the Tile Grout to harden. Remove excess Grout by wiping with a clean, damp cloth or sponge. Allow to cure 12 hours, polish tile with a clean, dry cloth.

COVERAGE

Average coverage on ceramic tile – 12-15 sq. ft. per pound.

Average coverage on mosaic tile – 4-6 sq. ft. per pound.

TECHNICAL DATA

Percent Non-Volatile by Weight – 100%
Percent Non-Volatile by Volume – 100%
Density – 2.7 pounds per cubic Feet
Contains No Asbestos

CAUTION

Contains Portland Cement. Avoid contact with eyes. In case of eye contact, flood eyes repeatedly with water and call a physician.

KEEP OUT OF THE REACH OF CHILDREN.

FIRST AID: In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

AVAILABILITY

UGL Powder Tile Grout is available in a 4 pound plastic pail. It may be purchased in hardware stores, home centers, paint stores and lumberyards.

PRODUCT DATA
UGL POWDER TILE GROUT

