



# PRODUCT DATA SHEET

## UGL® LATEX TUB AND TILE CAULK

### DESCRIPTION

UGL Latex Tub and Tile Caulk is a nonstaining, silicone-fortified sealant. This mildew-resistant compound stays white and provides excellent adhesion to most building materials. Tub and Tile Caulk goes on easily and forms a water tight seal. It bonds to metal, wood, masonry, tile or glass.

Tub and Tile Caulk can be used on a variety of interior and exterior surfaces including window and door frames, sinks, tubs and showers.

### SURFACE PREP

Opening to be sealed must be dry and free of moisture, dirt, grease, dust, soap film and loose caulk.

Rubbing alcohol is recommended to remove soap film.

### APPLICATION

Place spout-tip at an angle over area to be sealed. If area is deeper than 1/4-inch fill space with oakum or backing material up to 1/4-inch deep. Start at the bottom of the area to be sealed and work up as the void is filled. Wipe off excess caulk with a damp cloth before it dries (approximately 30 minutes). Note: Knead tube in hand before applying.

After caulk is applied, wait one hour before painting with a latex paint. Wait overnight before temperature and/or high humidity will extend drying time. Apply only when air and surface temperatures are above 50° F (10° C).

To reset tile, apply liberally at center and each corner. Place tile firmly in proper position. Clean tools with soap and water upon completion.

### TECHNICAL DATA

Percent non-volatile by weight: 82.6%

Percent non-volatile by volume: 71.0%

Consistency: Soft Paste

Density: 13.6 lbs./gal.

Coverage: 36 lineal feet with 1/4-inch bead

### CAUTION

Do Not Take Internally

Keep Out of The Reach of Children

### AVAILABILITY

UGL Tub and Tile Caulk is available in white in a six-ounce squeeze tube. It may be purchased in hardware stores, home centers, paint stores and lumber yards.

PRODUCT DATA  
UGL LATEX TUB AND TILE CAULK

LR 10/00



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com