



# PRODUCT DATA SHEET

## GLAZOL® PAINTER'S PUTTY

### DESCRIPTION

UGL Glazol Painter's Putty is a ready-to-use, smooth, easy-working formula designed specifically for professional painters.

For interior or exterior applications on old and new wood surfaces and on drywall. Use Glazol Painter's Putty to fill small cracks, patch nail holes, countersunk primed nail heads, shallow hammer marks and other minor defacements on a variety of surfaces. Perfect for use on windowsills, wood decks, wooden steps and woodwork. Glazol may also be used to glaze wooden window sashes.

It forms a perfect cushion against shock and vibration when used in replacing broken glass. Glazol Painter's Putty does not contain water to stay fresh so rust will not form on nail heads or in the can. Glazol Painter's putty remains pliable-does not chip or crack and has year-round workability.

### SURFACE PREP

#### For use as a Wood Filler

Be sure surface is firm, clean and dry. Remove all dirt, dust, grease, oil, mildew, wax and loose material. Sand glossy painted surfaces to improve adhesion. New or unpainted wood must be primed.

**APPLICATION:** Air and surface temperature should be above 40°F. Place Glazol Painter's Putty in hands, roll to warm and soften and form the shape of a point. Press Glazol onto surface with finger or thumb. Smooth Glazol with a clean putty knife while wet. When properly applied, the patch should be filled to the surface around it, eliminating the need to sand. Glazol Painter's Putty should be primed and painted after it is applied to maintain durability.

#### For use as a Glazing Compound

Surface must be clean and dry. Remove all old putty and bedding. Air

and surface temperature should be above 40°F. For best results surface should be primed with a quality wood primer.

**APPLICATION:** Place Glazol Painter's Putty in hands and roll to warm and soften. Apply a thin layer to backstop of sash filling height and width of L-shaped recess completely. Press glass firmly in place.

Install glazier's points to hold glass in place. Smooth Glazol Painter's Putty to an angle that sheds rain and glaze corners to a round finish. Glazol Painter's Putty should be primed and painted after it is applied to maintain durability. NOTE: Glazol Painter's Putty is not for use on any surface other than wood. Do not use on insulated glass units with an organic seal, plastic window panes or any window pane over 48" in any direction.

### WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### DRYING

Allow Glazol Painter's Putty to dry to form a protective skin (top drying) for a firm set. Surface drying of the Glazol Painter's Putty may be slowed by cold, damp weather, and by the size and depth of the fill/patch. Allow to dry overnight before painting with oil base paint and 24 hours before applying a latex paint.

### CLEAN-UP

Before setting, excess material may be removed with mineral spirits. After setting, material must be cut, sanded or scraped away.

### COVERAGE

When applied according to directions, one quart will fill up to 56 cubic inches.

### PHYSICAL PROPERTIES

Viscosity	Putty
% Solids by Weight	98 to 99
% Solids by Volume	95 to 97
Coverage	56 cubic inches
Recommended Film Thickness	<1/4 inch void
Dry time (to touch)*	overnight
Dry time (to apply paint)*	24 to 48 hours
Dry time (to maximum hardness)	>1 week
VOC	1.4% by weight

### IMPORTANT

To minimize skinning of unused material, cover with aluminum foil or plastic wrap before replacing lid.

### CAUTION

RAGS, STEEL WOOL OR WASTE SOAKED WITH UGL GLAZOL PAINTER'S PUTTY MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

Do not take internally. Close container after each use.

### AVAILABILITY

UGL Glazol Painter's Putty Compound is available in quart containers. It is sold in hardware stores, home centers, paint stores and lumberyards.

LR 2-09



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
[www.ugl.com](http://www.ugl.com)

PRODUCT DATA  
GLAZOL® PAINTER'S PUTTY