



# PRODUCT DATA SHEET

## ZAR® DECK & SIDING CLEAR WOOD SEALER & NATURAL TONER BASE

### DESCRIPTION

ZAR Deck & Siding Clear Wood Sealer & Natural Toner Base accents the natural grain, texture and beauty of wood. Protects exterior wood surfaces from the effects of rain, sun and other weather damage.

Specially formulated to resist mildew growth on the dry sealer film with the incorporation of a nonhazardous, green biocide( ISP CLEANGUARD) . Apply to new or old wood that has been left unstained and unpainted. Ideal for pressure treated lumber, pine, redwood, cedar and composite deck materials.

ZAR Deck & Siding Clear Wood Sealer & Natural Toner Base is ideal for decks, rails, posts, fencing, gazebos, sheds, wooden shingles, shakes and other exterior unstained or unpainted wood surfaces.

Will not harm plants or shrubs.

### SURFACE PREP

Surface must be clean, dry and in good condition. Remove all mildew, dirt, dust, loose wood fibers, paint flakes, mill glaze, oil and grease. Test the wood for factory treatment by sprinkling a few drops of water on the surface. If water is readily absorbed into the wood, proceed. If not, DO NOT apply ZAR

Deck & Siding Clear Wood Sealer & Natural Toner Base. Wait 1 month and then retest. Repair or replace any loose , cracked or warped boards. All mildew (dark, fuzzy or powdery deposits) must be removed with the following solution; 1/3 cup heavy-duty laundry detergent to 1 quart household bleach to 3 quarts of warm water, or use ZAR Deck & Siding Cleaner. Apply with a scrubbing brush. Rinse thoroughly and allow to dry before applying Clear Wood Sealer. Wear protective eye goggles and waterproof gloves when handling cleaning solution.

For Old Grayed Wood Exposed to UV (Sunlight) for more than 3 months: Power wash the surface to remove the thin layer of degraded wood and clean surface as above. Allow the wood to dry thoroughly after power washing before applying ZAR Clear Wood Sealer & Natural Toner Base.

**WARNING!** If you scrape,sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

Wear a NIOSH- approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION

Apply only when surface and air temperatures are above 50°F and less than 90°F. **DO NOT THIN. STIR THOROUGHLY** before and during application. Do not apply if rain is expected within 24 hours. Avoid applying in direct sunlight. Apply using a brush, roller, foam pad applicator or by spray. If sprayed, coating should be dry brushed or back rolled for uniform appearance. One coat will protect and beautify the wood while allowing the natural grain to show through. An additional coat will slightly darken the appearance and provide extended protection. On vertical siding, start at the top on several boards and apply continuously to bottom. On horizontal siding, start at one corner on several boards and apply continuously across to break at door, window or corner. Be sure to maintain a wet edge.

### AS A NATURAL TONER TINT BASE

Test the tinted ZAR Deck & Siding Clear Wood Sealer & Natural Toner Base on a sample piece of wood or in an inconspicuous area to determine final color. When using two or more gallons of the same tinted ZAR Clear Wood Sealer & Natural Toner Base , mix together to ensure color uniformity.

### TECHNICAL DATA

Viscosity: 60KU.

% Non-Volatile by Weight-28.0%-29.0%

% Non-Volatile by Volume-26%-27%

Coverage: 300 square feet per gallon.

On less porous woods coverage could be greater.

Dry time ( to touch)\*

Dry time ( to recoat)\*

VOC Content Does not exceed 100g/L

Weight per gallon-8.6lbs

\*Dry time: Allow 2 hours drying time. May be recoated in 4 hours. Drying time will be affected by temperature, humidity and film thickness. On decks allow to dry 24 hours before use.

### CLEAN-UP

Use warm soapy water.

### MAINTENANCE

Areas with harsh exposure to sun, weather or foot traffic will show wear more quickly than other surfaces.

If this occurs, clean affected areas and recoat as necessary.

### CAUTION

Do not take internally. Close container after each use. **KEEP FROM FREEZING.**

Please read the Material Safety Data Sheet for additional information.

### AVAILABILITY

ZAR Deck & Siding Clear Wood Sealer is available in quarts and gallons It may be purchased at hardware stores, home centers, paint stores and lumber yards.

LR811



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
[www.ugl.com](http://www.ugl.com)

PRODUCT DATA  
ZAR DECK & SIDING CLEAR SEALER/TONER