



PRODUCT DATA SHEET

ZAR® RAIN STAIN SOLID COLOR 100% ACRYLIC EXTERIOR STAIN

DESCRIPTION

ZAR Rain Stain Solid Color 100% Acrylic Exterior Stain is specially formulated to bring out the natural texture of wood grain. Rain Stain shields against the damaging effects of rain, snow, mildew, salt air and ultraviolet rays.

For use inside or outside on new or previously stained or painted wood, textured hardboard, properly prepared concrete, stucco, cement and cinder block, adobe, brick and aged galvanized metal, aluminum, vinyl and T-111 siding, plastic gutters and downspouts. Covers like paint yet accents wood texture. ZAR Rain Stain Solid Color Exterior Stain is rated number one for overall properties by a leading consumer research group. It does not oxidize - produces a breather type film to prevent cracking, peeling and blistering. Cleans up with soap and water, covers 300 to 400 square feet per gallon over smooth surfaces, 100 to 200 square feet per gallon over rough surfaces.

Note: On wood floors, decks, posts and railings, use ZAR Deck Stain.

SURFACE PREP

Clean painted, stained or varnished surfaces thoroughly. Dull glossy surfaces with sandpaper. If the previous coating is loose or flaking, it must be completely removed. All surfaces must be free from dust, dirt, loose wood fibers, oil and grease. Mildew (dark, fuzzy or powdery deposits) must be removed either by using ZAR Deck Cleaner according to the manufacturer's directions or by using the following washing solution: 1 quart household bleach and 1/3 cup UGL MEX® All Purpose Cleaner to 3 quarts warm

water. Apply with scrubbing brush, rinse thoroughly and allow to dry before staining. Pre-treatment with a water repellent or preservative is not recommended. Use ZAR Rain Stain 796 Primer/Sealer before applying ZAR Rain Stain on new woods prone to bleeding such as Redwood, Cedar and Fir and under all light-colored or pastel shades.

APPLICATION

Apply only when air and surface temperatures are above 50°F. DO NOT THIN. Stir thoroughly before using and stir occasionally while applying; making certain all pigment is incorporated.

ZAR Rain Stain may be applied by brush, roller or spray. However, application with a synthetic bristle brush is recommended. Avoid applying in direct sunlight. On vertical siding, start at top on several boards and apply continuously to bottom.

On horizontal siding, start at corner of several boards and apply continuously across to a break at a door, window or corner. Be sure to maintain a wet edge.

For best results and maximum durability, apply two coats. Color uniformity depends on uniform application.

It is important to prevent lap marks during application. When using more than one container of the same color, intermix for color uniformity. If spraying, reduce up to 10% with clean water. The coating should be dry brushed or back rolled for color uniformity.

CLEAN-UP

Clean application tools immediately after use in warm, soapy water. If material has dried, clean the tools using UGL FASTRIP® Brush Cleaner.

COVERAGE

Smooth surfaces: 300 - 400 square feet per gallon.

Rough surfaces: 100 - 200 square feet per gallon.

DRY TIME

Drying time is one to two hours. You may recoat after two hours.

LIMITATIONS

Do not use on floors, decks, rails or roofs.

Do not intermix with other kinds of stains.

On brushed or abraded plywood, apply only one coat (by brush) of ZAR Rain Stain Semi-Transparent Acrylic Stain.

Do not use a water repellent or preservative before applying ZAR Rain Stain. Do not freeze.

Do not apply to horizontal surfaces.

Do not use on benches or outdoor furniture.

Do not use on smooth-surfaces, factory-primed hardboard. Instead, topcoat with a premium house paint.

CAUTION

Do not take internally.

Avoid prolonged contact with skin or breathing of spray mist.

Close container after each use.

Keep from freezing.

KEEP OUT OF REACH OF CHILDREN.

PRODUCT DATA
ZAR RAIN STAIN SOLID COLOR

ZAR® RAIN STAIN SOLID COLOR 100% ACRYLIC EXTERIOR STAIN

TECHNICAL DATA

Percent Non-Volatile by Weight: 55.5
Percent Non-Volatile by Volume: 38.0
Density: 11.7 lbs. per gallon
Viscosity: 78 KU @ 77°F.
Does Not Exceed Maximum VOC 350 g/l;
VOS 2.9 lbs./g
Complies with current Volatile Organic
Compound (VOC)/Volatile Organic Solvent
(VOS) regulations.
Complies with California air pollution
regulations.

AVAILABILITY

ZAR Rain Stain Solid Color 100% Acrylic Exterior Stain comes in eight ready mixed colors. Using Rain Stain tint bases and tinting formulas, 22 additional colors are available at your favorite paint store, home center, hardware store and lumberyard. ZAR Rain Stain tint base may also be used for custom coloring. Rain Stain Solid Color ready mixed colors are available in one and five gallon containers. Tint bases are available in quarts, gallons and 5-gallon containers.

WARRANTY

UGL, makers of ZAR Rain Stain Solid Color Exterior Stain, warrants this product when applied according to manufacturer's directions, for 15-years against cracking, peeling and blistering. UGL will at its option, provide additional product at no charge or refund the purchase price. This warranty does not include labor or cost for application of any ZAR

Rain Stain Solid Color Exterior Stain. Claims must be made in writing and include proof of purchase. This is the exclusive remedy.

