



PRODUCT DATA SHEET

ULTRA ZAR® PLUS STAIN & POLYURETHANE IN ONE

DESCRIPTION

ULTRA ZAR PLUS is the fast and easy way to a beautiful finish. Our unique formula of stain and polyurethane in one lets you brush on rich color and lasting protection in less than half the time. No more staining and waiting with one product, then protecting with another. ULTRA ZAR PLUS comes in six popular colors in either Gloss or Satin finish, available in quarts, pints and half-pints. ULTRA ZAR PLUS enhances the beauty of interior wood surfaces. Over old varnish, use ULTRA ZAR PLUS to change or darken the color without removing the old finish. Do not use over shellac or lacquer.

SURFACE PREP

Remove lacquer, shellac, or old varnish finishes in poor condition with ZAR Paint Remover. Wipe off residue. Sand bare with fine sandpaper in the direction of the grain. Sand old varnish finishes in good condition to remove gloss. Wipe off sanding dust with a tack cloth. Surface must be clean, dry, and free of wax, dirt, oil, polish, grease or any finish that is not compatible with a polyurethane coating.

APPLICATION

Stir well (do not shake), apply only when the temperature is above 50°F. Check color by brushing on a first coat using long, uniform strokes in the direction of the grain, maintaining a wet edge. Brush out any lap marks. Avoid a buildup of ULTRA ZAR PLUS on the edges. Allow ULTRA ZAR PLUS to dry 2 hours. Then sand lightly, using fine sandpaper. Wipe off dust with a tack cloth. Apply a second coat, additional coats will give a darker color. Clean brush with mineral spirits or UGL Fastrip Brush Cleaner.

DANGER

Rags, steel wool or waste soaked with ULTRA ZAR PLUS may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

COVERAGE

One pint covers up to 75 square feet.

DRYING

Allow to dry 2 hours between coats. Allow final coat to dry 4-6 hours. Temperature, humidity and film thickness may affect drying time. If while sanding, sandpaper gums or surface feels tacky, extend drying times.

CAUTION

Contains Petroleum Distillate. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. If swallowed, do not induce vomiting; call physician immediately. Do not use or store near heat or flame. Use with adequate ventilation. Avoid prolonged contact with skin. In case of skin contact, wash with soap and water. If irritation persists, see physician.

AVAILABILITY

ULTRA ZAR PLUS is sold in hardware stores, paint stores, lumber yards and home centers.

PRODUCT DATA
ULTRA ZAR PLUS STAIN & POLYURETHANE

