



# PRODUCT DATA SHEET

## ZAR® TROWELABLE WOOD PATCH

### DESCRIPTION

ZAR Trowelable Wood Patch is a low odor, ready-to-use, full trowel latex patching compound for interior use only. The use of ZAR Trowelable Wood Patch, when patched area requires stain, greatly diminishes the lighter area or "halo" effect surrounding the patch normally present with other wood fillers.

### USE

Fills open-grain and nail holes. Repairs cracks and gouges on wood surfaces. May be sanded, nailed, sawed, drilled, will take paint, varnish, shellac, polyurethanes and stain.

### PREPARATION

Remove all dirt, dust, grease, oil and loose particles from the area. Dampen surfaces to be patched with water. Do not use when material, air or surface temperatures are below 50°F.

### APPLICATION

Pour ZAR Trowelable Wood Patch on the floor surface. Using a non-metallic, smooth edge finishing trowel spread the wood patch across the entire surface. Be sure to press ZAR Trowelable Wood Patch into the surface to fill all cracks. May be sanded after one hour. Deep areas should be filled in layers allowing each layer to dry between applications. Sand after last layer has completely dried. Final sanding should remove all ZAR Trowelable Wood Patch from the surface of the wood leaving the patch only in the surface cracks and nail holes.

### NOTE

Always wear an approved (NIOSH/MSHA) dust mask while sanding. Avoid breathing sanding dust. Keep product out of reach of children.

### STAINING

When staining after patching, it is advisable to wipe off excess patching material with a damp cloth immediately after application. When dry, sand patch with medium sandpaper. Allow overnight drying before applying an oil-based stain, paint, varnish, shellac or polyurethane - 1 1/2 to 2 hours before applying a latex stain or paint.

### CLEAN-UP

To remove excess or to clean hands or tools, simply wipe with a damp cloth before material dries. Close container after each use. Keep from freezing.

### COVERAGE

Covers up to 2600 sq. ft. per 3.5 gallon containers, depending on the porosity of wood, sizes and/or number of cracks or gaps to be filled.

### AVAILABILITY

ZAR Trowelable Wood Patch is available in gallon containers in Red Oak and White Oak and 3.5 gallon containers in Red Oak, White Oak and Maple/Ash/Pine.

PRODUCT DATA  
ZAR TROWELABLE WOOD PATCH

LR 2/07



United Gilsonite Laboratories:  
Corporate Headquarters  
1396 Jefferson Avenue  
Dunmore, PA 18509  
Tel: 1-800-272-3235  
www.ugl.com