



PRODUCT DATA SHEET

ZAR® QUICK DRY POLYURETHANE SANDING SEALER

DESCRIPTION

ZAR Quick Dry Polyurethane Sanding Sealer is for interior use only. A fast drying sanding sealer for floors, furniture, paneling, cabinets, counter tops and woodwork. Dries in one hour on bare wood. Use as a first and/or second coat under Interior ZAR Gloss, Semi-Gloss, Satin or Antique Flat Polyurethane and under ZAR ULTRA Gloss, Semi-Gloss or Satin. ZAR Quick Dry is available in Semi-Gloss and Satin Sheens.

SURFACE PREP

New Wood: Sand smooth using fine sandpaper and wipe clean all sanding dust with tack rag or cloth dampened with mineral spirits.

Old Clear Finishes in Good Condition: Remove grease, dirt and wax. Sand lightly in the direction of the grain to remove any gloss. Clean sanding dust with tack rag or cloth dampened with mineral spirits.

TECHNICAL DATA

Old Clear Finishes in Poor Condition, Lacquer or Shellac: Remove completely. If the old finish contains wax or stearates, regardless of condition, remove completely. Sand and remove all sanding dust.

Do not apply over wood fillers or finishes containing stearates.

APPLICATION

Stir thoroughly before and during application. Do not shake! Apply straight from the can. DO NOT THIN. May be applied by brush, pads, lambs wool applicator or spray. Flow ZAR on in the direction of the grain. Sand lightly between coats. Dust and wipe clean. If more than 24 hours elapse between coats, sand thoroughly and clean.

APPLICATION

ZAR Quick Dry Polyurethane Sanding Sealer is part of UGL's complete line of ZAR Wood Finishing products. It is available at hardware stores, home center, paint stores and lumberyards.

DRYING

Allow first coat to dry 1 hour. Succeeding coats up to 2 hours. Temperature, humidity and film thickness may affect drying time. If while sanding, sandpaper gums or surface feels tacky, extend drying times.

CLEAN-UP

Clean brushes and tools immediately after use with paint thinner or mineral spirits.

COVERAGE

2500-3000 sq. ft. per 5 gallon.

CAUTION

Use only with adequate ventilation. Keep out of reach of children.

PRODUCT DATA
ZAR QUICK DRY POLY. SANDING SEALER

COMPOSITION OF ZAR QUICK DRY POLYURETHANE SANDING SEALER

ZAR Semi-Gloss Quick Dry Polyurethane Sanding Sealer

Non-Volatile:	100% Pure ASTM Type 1	
	Polyurethane Resin	39.7%
	Additives	0.6%
Volatile:	Aliphatic Hydrocarbon Solvents	59.7%
		<u>100.0%</u>

ZAR Satin Quick Dry Polyurethane Sanding Sealer

Non-Volatile:	100% Pure ASTM Type 1	
	Polyurethane Resin	39.6%
	Additives	0.6%
	Flattening Agent	1.0%
Volatile:	Aliphatic Hydrocarbon Solvents	59.7%
		<u>100.0%</u>

