



PRODUCT DATA SHEET

ZAR® TUNG OIL WIPE-ON FINISH

DESCRIPTION

ZAR® Tung Oil Wipe-On Finish wipes on with a cloth for a beautiful finish every time. Fortified with polyurethane, ZAR Tung Oil Wipe-On Finish is ideal for bartops, furniture, paneling, cabinets, wood floors*, woodwork, spindles and antiques. Resists ring marks caused by hot, cold or alcoholic beverages.

A damp cloth renews the finish. Child safe when dry. ZAR Tung Oil Wipe-On Finish can also be used as a one coat wood conditioner for bare, soft or porous wood to achieve a uniform stain appearance.

SURFACE PREP

New Wood: Sand smooth using fine sandpaper. Remove sanding dust with tack rag or cloth dampened with paint thinner or mineral spirits.

Old Finishes in Good Condition: Remove grease, dirt and wax. Sand lightly in the direction of the grain to remove any gloss. Clean and remove dust as above.

Old Finishes in Poor Condition: Remove completely. Sand and remove dust as above. As a wood conditioner for bare soft and porous wood: For a uniform wood stain appearance, prior to staining bare soft and porous wood such as fir, pine, lauan and aspen, wipe on a coat. Wait 5-10 minutes, then wipe off excess. Apply stain within 2 hours.

APPLICATION

Apply when air and surface temperatures are above 50°F. Stir before and during application. Do not shake! Do not thin. Apply straight from the can. Apply using a clean lint-free cloth (an old tee shirt works well). Do not use a roller. For floor application use a lambswool applicator or the ZAR® Fast Pad.

DRYING

Allow to dry 6-8 hours depending on temperature, humidity and film thickness. If while sanding, sandpaper gums or surface feels tacky, extend drying time.

CLEAN-UP

Clean immediately after use with paint thinner or mineral spirits.

COVERAGE

Up to 800 sq. ft. per quart.

CAUTION

Use only with adequate ventilation. Keep out of reach of children.

ZAR® TUNG OIL WIPE-ON FINISH

ZAR FINISHES SELECTOR

	OUTDOOR USE	INDOOR USE	USED ON FLOORS	HOW TO APPLY	APPEARANCE OF FINISH
Semi-Gloss Polyurethane	No	Yes	Yes*	Cloth	Semi-Gloss
Satin Polyurethane	No	Yes	Yes*	Cloth	Satin

TECHNICAL DATA

COMPOSITION OF ZAR POLYURETHANE CLEAR WOOD FINISHES

ZAR Tung Oil Semi-Gloss Wipe-On Finish

Non-Volatile:	Tung Oil Varnish	21.9%
	100% Pure ASTM Type 1	
	Polyurethane Resin	7.3%
	Additives	1.2%
Volatile:	Aliphatic Hydrocarbon Solvents.....	69.6%
		<u>100.0%</u>

ZAR Tung Oil Satin Wipe-On Finish

Non-Volatile:	Tung Oil Varnish.....	19.0%
	100% Pure ASTM Type 1	
	Polyurethane Resin	6.3%
	Modified Linseed Oil	3.8%
	Flatting Agent.....	1.2%
	Additives.....	1.9%
Volatile:	Aliphatic Hydrocarbon Solvents.....	67.8%
		<u>100.0%</u>

PRODUCT CHARACTERISTICS

	Semi-Gloss	Satin
Percent Non-Volatile by Weight	29.5%	31.3%
Percent Non-Volatile by Volume	24.0%	25.0%
Weight Per Gallon	7.07 ± 0.2	7.13 ± 0.2
Viscosity (Gardner Holdt)	A ⁴ @ 77°F	A ⁴ @ 77°F
Volatile Organic Content (g/L)	597	587
Volatile Organic Substances (lbs./gallon)	5.0	4.9

AVAILABILITY

ZAR Tung Oil Wipe-On Finish is part of UGL's complete line of ZAR Wood Finishing products. Available at hardware stores, home centers, paint stores and lumberyards.

* Note: ZAR Tung Oil Wipe-On Finish provides beautiful protection on wood floors. Though not as durable as a full bodied polyurethane, it is perfect for use where a "Penetrating Oil Finish" is desired.

