



PRODUCT DATA SHEET

ZAR® ULTRA MAX FLOOR REJUVENATOR

DESCRIPTION

ZAR ULTRA MAX Interior Waterborne Oil-Modified Hardwood Floor Rejuvenator applies easily to restore and renew the beauty of wood that has become dull, scratched or show signs of wear. Perfect for restoring worn polyurethane floor finishes, shellac, lacquer and other factory prefinished wood surfaces* Exotic Hardwood Approved. Ideal for use on Teak, Brazilian Walnut, Brazilian Cherry and other exotic wood species. Features DUAL DRYING TECHNOLOGY for a harder "through cure".

SURFACE PREP

Old Clear Finishes in Good Condition: Remove grease, dirt and wax. Vacuum and wash the surface with an oil free cleaner and a damp mop. Sand lightly in the direction of the grain to remove any gloss and wipe clean with a tack cloth (Do Not Use Steel Wool)

Old Lacquer or Shellac: Test compatibility in an inconspicuous area. If acceptable, prepare as directed under Old Clear Finishes in Good Condition.

Old Clear Finishes in Poor Condition: Remove completely. *NOTE: Test compatibility in an inconspicuous area such as a closet. Not recommended over waxed or oiled floors. Test for wax by sprinkling a few drops of water on the surface, wait 10 minutes, if surface turns white it indicates wax may be present which must be completely removed. Badly worn floors require a complete refinishing.

APPLICATION

Apply above 50°F and below 90°F. Gently rock container back and forth to mix. Do not shake! Squeeze a liberal amount of ZAR ULTRA MAX directly on the wood surface in an "S" pattern. Spread evenly with a long handle synthetic applicator pad or painter's pad. Smooth the finish in the direction of the wood grain. Work in 4' x 4' sections, working towards an exit. Apply thin coats. Do not allow to puddle. Allow to dry 2 hours between coats. Sand lightly and wipe clean with a tack cloth between coats. Apply 2 coats. For greater protection apply additional coats.

DRYING

Dry to Touch 1 to 2 Hours
Dry to Recoat 2 Hours
Dry to Light Traffic 24 Hours
Dry to Heavy Traffic (furniture placement) 3 to 5 days

CLEAN-UP

Clean brushes and tools immediately after use with warm soapy water.

TINTING

DO NOT THIN
For additional information please refer to the Material Safety Data Sheet.

CAUTION

CONTAINS SMALL AMOUNTS OF TRIPROYLENE GLYCOL METHYL ETHER, and N-METHYLPYRROLIDINONE . Vapor may be harmful. May affect the brain or nervous system causing dizziness, headache or nausea. May cause nose throat and eye irritation. May be harmful if absorbed through skin. Harmful if swallowed. Use only with adequate ventilation.

Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. This product contains chemicals known to the State of California to cause birth defects and reproductive harm.

FIRST AID

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

If spilled, contain spilled material and remove with inert absorbant. Dispose of contaminated absorbant, container and unused contents in accordance with local, state and federal regulations.

ZAR® ULTRA MAX FLOOR REJUVENATOR

PRODUCT CHARACTERISTICS

Viscosity	11-15 seconds #4 Ford Cup to 60 Ku
pH	8.0 to 8.5
% Solids by Weight	28 to 30
% Solids by Volume	28 to 30
Coverage	200 to 300 ft.2/Quart/Coat
Recommended film thickness/coat	≈2 wet mils
VOC Content	<250 g/L

Sheen Ranges:

Gloss 85+ at 60°

Satin 40 to 50 at 60°

AVAILABILITY

ZAR ULTRA MAX Floor Rejuvenator can be purchased at paint stores, hardware stores, home centers and lumberyards.

