



PRODUCT DATA SHEET

ZAR® LATEX WOOD PATCH

DESCRIPTION

ZAR Wood Patch is a ready-to-use latex patching compound containing treated pulverized wood. ZAR Wood Patch is excellent for many uses because it shrinks less, and may be nailed, sawed, sanded, or drilled. ZAR Wood Patch will take paint, varnish, shellac, polyurethanes, stains and can be used indoors or outdoors. When a patched area requires stain, ZAR Wood Patch greatly diminishes the lighter area of "halo" effect surrounding the patch normally present with other wood fillers. ZAR Wood Patch is neutral in color and non-flammable. Neutral available in 3-ounce plastic tubes, and ¼ pint, ½ pint, pint, quart, and gallon containers. Red Oak and Golden Oak color available in quarts, gallons, and 3-ounce squeeze tubes.

ZAR Wood Patch . . .

FILLS: Cracks, dents, holes, gouges, broken edges, and chipped corners.

REPAIRS: Toys, patterns, furniture, picture frames, most items made from wood.

REPLACES: Rotted wood-carpentry mistakes.

MAKES: Inlays, models, novelties, carved objects.

PREPARATION

Remove all dirt, grease, oil and loose particles from the patch area. Dampen surfaces to be patched with water. Do not use when material and/or air temperature is below 40°F. ZAR Wood Patch can be tinted with universal colorants or colors used in latex paints.

APPLICATION

Apply with trowel, putty knife or use 3-ounce tube to apply patch directly into imperfection. Press compound tightly into place, building up patch slightly higher than surrounding area. Patches under ¼" wide and deep will usually require just one application. May be sanded after one hour. Deep areas should be filled in layers allowing each layer to dry between applications. Sand after each layer has completely dried. Allow overnight drying of patch before applying an oil base stain - 1½ to 2 hours before applying latex paint. All exterior application must be top-coated.

NOTE

In addition to being used as a wood patching compound for cracks and nail holes, ZAR Latex Wood Patch may also be used as a wood filler for open-grained woods such as oak and mahogany.

To use as a wood filler, reduce ZAR Latex Wood Patch with water so that a creamy consistency is obtained. Apply against the grain so that the material fills the pores of the wood. Let set for 5-10 minutes and scrape off excess material in the direction of the grain with a non-metallic scraper. Allow to dry overnight. Sand lightly and apply ZAR Wood Stain and/or ZAR Polyurethane.

CLEAN-UP

To remove excess or to clean hands or tools, simply wipe with damp cloth before material dries. Close container after each use.

PRODUCT DATA
ZAR LATEX WOOD PATCH

LR 4/02



United Gilsonite Laboratories:
Corporate Headquarters
1396 Jefferson Avenue
Dunmore, PA 18509
Tel: 1-800-272-3235
www.ugl.com