

UGL® Masonry Crack Filler

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

Drylok Masonry Crack Filler is formulated to seal and waterproof cracks in concrete walks, steps, floors and to replace cracked mortar joints. Reduces radon gas penetrartion. Fast easy clean up with water. Easy gunning with excellent adhesion, even to damp surfaces.

- Seals and waterproofs cracks in masonry walls, sidewalks, steps and floors
- Replaces cracked mortar joints
- May be painted over immediately with latex paint
- Excellent adhesion even to damp surfaces
- Reduces radon gas penetration

BASIC USES

The product seals and waterproofs interior and exterior cracks in concrete walks, steps, floors and replaces cracked mortar joints.

LIMITATIONS

Do not store in areas of extreme heat or cold. Not to be used as a substitute for high temperature furnace cement or fireplace mortar.

TECHNICAL DATA

COMPOSITION:

Acrylic fortified with silicone

SHEEN:

N/A

% WEIGHT SOLIDS:

83%

% VOLUME SOLIDS:

72%

DENSITY (LBS./US GAL.):

13.4

VISCOSITY:

N/A

pH:

7.5

COLORS:

- Gray

CURE TIME:

- 12 Hours

Note: Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE:

- 48 Linear ft. per 1/4" bead

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

3 Year- unopened container

FREEZE/THAW:

Protect from freezing

CONTAINER SIZES:

Ten and one-half fluid ounces (US) caulk tube

VOC

57 g/L

TINTING

N/A

SURFACE PREPARATION

Opening to be sealed must be free from frost, dust, dirt, oil and loose particles.

Hosing and wire brushing facilitate cleaning.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Place cartridge in any standard style caulk gun. Select the size of the bead by cutting the plastic spout at the number indicated (5/16, 1/4) on the cartridge tip. Cut spout at a 45-degree angle. Puncture inner seal in spout with screwdriver. Force compound tightly into the crack. Smooth down patch with a wet putty knife or trowel.

DRYLOK Masonry Crack Filler is non-flammable. It should not, however, be used as a substitute for high temperature furnace cement or fireplace mortar. Deep cracks (over 1/4") should be filled to within 1/4" of top with Oakum before filling with crack filler.

VENTILATION

N/A

CAUTION

DO NOT TAKE INTERNALLY. KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.



CURE TIME:
12 Hours



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application



SPREAD RATE:
48 Linear Feet/
1/4 Inch Bead

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulators.

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected area with soap and water. Consult a physician if irritation persists.

INGESTION: Drink 1 or 2 glasses of water. If individual is drowsy or unconscious do not give anything by mouth. Consult a physician, medical facility or poison control center for advise about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

Use contents of cartridge as directed within one year from date of purchase. If this material fails within 25 years of application, UGL will replace an equal amount of material free of charge. Return cartridge and proof of purchase to UGL. Liability is limited to replacement of product. This warranty applies to residential use only.

SPECIFICATION

N/A



Masonry Crack Filler
10.5 FL. OZ. CARTRIDGE 10/Case30507



Masonry Gray

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.