

## UGL® Gold Paint

## MANUFACTURER

## UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



UGL®



## PRODUCT DESCRIPTION

UGL Gold Paint is a gold, leaf-finish coating for interior decorative use. UGL Gold Paint remains stable. It will not tarnish in the container.

- Brilliant gold leaf-like finish
- Ideal for indoor decorative use
- Remains stable, will not tarnish in the container

## BASIC USES

Ideal for craft use, picture frames, toys, furniture trim, etc.

## LIMITATIONS

Interior surfaces only.

## TECHNICAL DATA

## COMPOSITION:

Oil base

## SHEEN:

N/A

## % WEIGHT SOLIDS:

44%

## % VOLUME SOLIDS:

20%

## DENSITY (LBS./US GAL.):

9.21

## VISCOSITY:

25 sec. Ford #4 cup at 77° F

## COLORS:

- Gold

## DRY TIME:

- Recoat: 24 hours

**Note:** Maximum cure and dry time will be prolonged when slightly humid and/or damp, cool conditions prevail.

## CLEAN UP:

Paint thinner

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## COVERAGE (SQ. FT./US OZ.):

- 6 sq. ft./2 oz.

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

## RECOMMENDED FILM THICKNESS/COAT:

13-21 Wet mils/coat

## FLASH POINT:

114°F

## SHELF LIFE:

N/A

## FREEZE/THAW:

N/A

## CONTAINER SIZES:

Two ounce (US) bottle

## VOC

Does not exceed 620 g/L

## TINTING

N/A

## SURFACE PREPARATION

Surface to be painted should be clean and free from all dirt, dust, grease, wax, etc. Stir well before using and frequently during use.

## WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA

vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

Apply evenly with a good, soft bristle brush. Brush on paint using minimum pressure, making sure the final brush strokes are made toward the previously applied paint. A second coat may be applied after 24 hours drying time. For spraying, reduce 10 percent with pure turpentine.

Clean brushes with turpentine. To avoid spontaneous combustion during temporary storage, soak soiled rags and wastes immediately after use in a water-filled closed metal container.


## CAUTION

CONTAINS PETROLEUM DISTILLATES! Vapor harmful. Keep away from heat and flame. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose, throat and skin irritation. Overexposure may cause kidney damage. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/ mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash



## DRY TIME:

12-24 hours  
Recoat 12 Hours



## CLEAN-UP:

Paint Thinner



## COVERAGE:

2 Coats Minimum



## SPREAD RATE:

6 Sq. Ft./2 Oz.

thoroughly after handling.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Use only with adequate ventilation.

This product contains a chemical known to the state of California to cause cancer, reproductive or developmental toxicity.

CLOSE CONTAINER AFTER USE.  
KEEP OUT OF REACH OF CHILDREN.

### DANGER

Combustible. Do not use near fire, sparks or flame. Use only in well-ventilated areas. Keep flow of fresh air until all vapors (odors) are gone. Do not transfer contents to unlabeled containers.

### FIRST AID

**EYES:** Flush immediately with large amounts of water for at least 15 minutes. Consult a physician.

**SKIN:** Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

**INGESTION:** Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

**INHALATION:** Remove to fresh air, restore breathing. Treat symptomatically. Consult a physician.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

### WARRANTY

N/A

### SPECIFICATION

N/A



#### Gold Paint

2 FL.OZ. 6/Case	.....	23503
1/2 PT. 6/Case	.....	23506
1 QT. 1/Case	.....	23512

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.