

UGL® Plaster Patch®

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

Plaster Patch is the original pure white, slow setting, glue base marble patching plaster. Plaster Patch can easily be troweled to a featheredge. Its greater plasticity prevents it from crumbling and rolling under the trowel. It is more adhesive because of its glue base.

- Slow setting patching material
- Dries pure white
- Easily trowel to a feather edge
- Plasticity prevents crumbling and rolling under trowel

BASIC USES

May be used for patching large defects on interior plaster walls.

LIMITATIONS

Plaster Patch is not recommended when smoothing wall surfaces or repairing fine cracks, small breaks and scratches in wood, wall board, plaster or masonry.

TECHNICAL DATA

COMPOSITION:

Oil base

SHEEN:

N/A

% WEIGHT SOLIDS:

100%

% VOLUME SOLIDS:

100%

DENSITY (LBS./US GAL.):

22.76

VISCOSITY:

Powder

pH:

N/A

COLORS:

White

SET TIME:

- 1½ hours

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Mineral spirits

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US LB.):

- 84 cu. in./lb.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

104°F

SHELF LIFE:

Indefinite in sealed container

FREEZE/THAW:

N/A

CONTAINER SIZES:

Four pound (US) plastic pail

VOC

N/A

TINTING

N/A

SURFACE PREPARATION

Remove all broken or loose plaster around area to be patched. Dampen the entire area including plaster and wooden laths with clean water.

MIXING: Add 3¼ cups of Plaster Patch to 1 cup clean water in a clean container.

Using a mixing paddle, stir thoroughly to form a stiff paste. Small amounts of Plaster Patch can be added to adjust consistency. Stir slowly and long enough to obtain the desired consistency. Prolonged mixing will speed up the set time.

IMPORTANT: Clean out all Plaster Patch that has set before remixing a new batch in the same container. If old mix, which has set, is not removed from the container a chemical reaction will take place causing the new batch to set much faster.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply with a trowel or putty knife. Force the Plaster Patch into the area. Smooth out the patch with the surrounding surface and allow patch to dry. After area has completely dried, sand patch smooth using fine sandpaper. For best results, spot prime before painting.

Setting time of Plaster Patch is approximately 1½ hours. Clean application tools immediately after use with warm, soapy water.



SET TIME:

1½ Hours



CLEAN-UP:

Soap and Water



COVERAGE:

1 Application



SPREAD RATE:

84 Cu. In./Lb.

Plaster Patch is specially formulated for repairing large defects in plaster walls. When smoothing wall surfaces or repairing fine cracks, small breaks and scratches in wood, wall board, plaster or masonry, use UGL 222 or 222 Lite Spackling Paste.

CAUTION

CONTAINS: Calcium Sulfate Alpha-Hemihydrate. When mixed with water this material hardens and then slowly becomes hot. **DO NOT** attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissues. When mixing or dry sanding, dust may cause irritation to eyes, nose throat or upper respiratory system.

Close container after each use. Avoid exposure to dust by wearing an appropriate NIOSH approved particulate respirator. Avoid with eyes and skin. When using, wear impermeable protective gloves, Wear goggles or protective glasses with side shields. Do not ingest.

**CLOSE CONTAINER AFTER EACH USE.
KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

SKIN: Wash affected areas with soap and water. Consult a physician if irritation persists.

INGESTION: Product hardens when wetted and if ingested may result in an obstruction.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Plaster Patch®
4 LB. 4/Case01417

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.