

## UGL® 222 Lite Spackling Paste

## MANUFACTURER

## UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



## PRODUCT DESCRIPTION

UGL 222 LITE Spackling Paste is a fast drying, lightweight compound for interior and exterior use.

For large holes and cracks, UGL 222 LITE smooths on easily, will not shrink, crack or crumble and requires little or no sanding.

- Lightweight, fast drying surface compound ideal for use on ceilings
- Will not shrink, crack or crumble
- Requires little or no sanding
- Patches cracked plaster, fills nail holes, repairs wall tile and more
- May be painted

## BASIC USES

The product is ideal for patching plaster, drywall, wood, Masonite, masonry and other construction surfaces.

## TECHNICAL DATA

## COMPOSITION:

Latex

## SHEEN:

N/A

## % WEIGHT SOLIDS:

43.8%

## % VOLUME SOLIDS:

72.3%

## DENSITY (LBS./US GAL.):

4.2

## VISCOSITY:

Stiff paste

## pH:

5.7

## COLORS:

White

## DRY TIME:

• 2 hours

**Note:** Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

## CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

## COVERAGE (CU. IN./US QT.):

• 56 cu. in./qt.

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

## RECOMMENDED FILM THICKNESS/COAT:

N/A

## FLASH POINT:

N/A

## SHELF LIFE:

N/A

## FREEZE/THAW:

Keep from freezing

## CONTAINER SIZES:

One-half pint (US), one pint (US), one quart (US) and one gallon (US) containers

## VOC

N/A

## TINTING

N/A

## SURFACE PREPARATION

Remove all loose dirt, paint, wax, grease and dust. Nail heads and other metal surfaces should be primed with a metal primer. UGL 222 LITE and surface temperature of area to be patched must be above 50°F.

All exterior applications must be painted.

## WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## APPLICATION

Stir and apply with a putty knife. Push UGL 222 LITE firmly into hole or crack, smoothing the material with long strokes of the putty knife. For extra-smooth finish, lightly smooth patched area with a wet putty knife.

UGL 222 LITE can be painted almost immediately with latex paint. Before applying an oil-based paint, allow material to dry thoroughly. For best results, prime patched areas. Allow these areas to dry thoroughly before sanding.

## CAUTION

Prolonged contact with skin during mixing or application may cause irritation some cases. If splashed on skin or in eyes, flush thoroughly with water.

DO NOT TAKE INTERNALLY.

AVOID BREATHING DUST

KEEP OUT OF REACH OF CHILDREN

## FIRST AID

**EYES:** Immediately flush eye thoroughly with



**DRY TIME:**  
2 Hours



**CLEAN-UP:**  
Soap and Water



**COVERAGE:**  
1 Application



**SPREAD RATE:**  
56 Cu. In./Qt.

water for at least 15 minutes. Consult a physician if irritation persists.

**SKIN:** Wash affected area with soap and water. Consult a physician if irritation is present.

**INGESTION:** Give 1 or 2 glasses of water to drink. If individual is drowsy or unconscious, do not give anything by mouth.

**INHALATION:** Remove to fresh air.

For additional health and safety information please refer to the "Safety Data Sheet".

**WARRANTY**

N/A

**SPECIFICATION**

N/A



**222 Lite Spackling Paste**

1/2 PT.	6/Case	.....	31806
1 PT.	6/Case	.....	31811
1 QT.	6/Case	.....	31812
1 GAL.	2/Case	.....	31813

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.