

UGL® MAR-GON Floor Leveler and Crack Filler

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

Mar-Gon Floor Leveler and Crack Filler levels floors prior to laying linoleum, tile, etc. Repairs wood furniture, picture frames, moldings, rotted wood, fills knot holes, nail holes, cracked or broken plaster. Also excellent for setting bathroom fixtures and casting patterns.

AS A FLOOR LEVELER: When mixed with water, Mar-Gon trowels on to level above-grade floors prior to laying linoleum, tile, and other floor coverings.

AS A REPAIR COMPOUND: Mar-Gon mixes easily with water to form a shrink-proof, quick-setting putty for repairing wooden furniture, picture frames, moldings and rotted wood. It also fills knot holes, nail and screw holes, wallboard joints and casting patterns. Mar-Gon's superior adhesion and durability also make it ideal for setting bathroom fixtures and repairing cracked or broken plaster around tubs and sinks.

- Highly adhesive, multi-purpose repair compound
- Level and repair wood, stone, concrete and plaster
- Set fixtures and casting patterns

BASIC USES

UGL Mar-Gon can be used indoors to level floors, repair wood, plaster, masonry and set casting molds.

LIMITATIONS

DO NOT use on surfaces subject to vehicular traffic or in locations exposed to wetness, such as below grade basement floors. DO NOT use this product if temperature will remain below freezing during application and for one week thereafter.

TECHNICAL DATA

COMPOSITION:

Powder, mix with water

SHEEN:

N/A

% WEIGHT SOLIDS:

100%

% VOLUME SOLIDS:

100%

DENSITY (LBS./US GAL.):

16.98

VISCOSITY:

N/A

pH:

7.5-8.5

COLORS:

White

SET TIME:

- 1 hour

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Soap and Water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (CU. IN./US LB.):

- 80 cu. in./4lb.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

Indefinite in sealed container

FREEZE/THAW:

N/A

CONTAINER SIZES:

Four pound (US) and 25 pound (US) plastic pails

VOC

N/A

TINTING

N/A

SURFACE PREPARATION

Remove all dirt, grease and foreign matter from area where Mar-Gon is to be applied. For best adhesion, dampen the area to be repaired with water. For best results on wood, prime first.

MIXING: In a clean receptacle, mix approximately three parts Mar-Gon to one part water. Stir quickly until a stiff, even paste is formed. For depressions in floors that are deeper than 1/4 inch, mix two parts clean, washed sand and one part floor leveler with water to a stiff, even paste.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your



SET TIME:
1 Hour



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application



SPREAD RATE:
80 Cu. In./ 4Lb.

family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

As a Floor Leveler: After applying and spreading Mar-Gon, smooth with a wet trowel. Reinforcing wire should be used when leveling large areas of wooden floors.

As a Repair Compound: Press Mar-Gon tightly into place with a trowel or putty knife and smooth surface as desired. Allow patch to set completely before using sandpaper or steel wool.

When fully cured (1 to 3 days after application depending upon temperature and humidity) Mar-Gon Floor Leveler and Crack Filler may be finished with any quality acrylic latex paint. When it is desirable to use an adhesive it is recommended that a water based acrylic latex adhesive be used.

CAUTION

CONTAINS: Calcium Sulfate Alpha-Hemihydrate. When mixed with water this material hardens and then slowly becomes hot. **DO NOT** attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissues. When mixing or dry sanding, dust may cause irritation to eyes, nose throat or upper respiratory system.

Close container after each use. Avoid exposure to dust by wearing an appropriate NIOSH approved particulate respirator. Avoid with eyes and skin. When using, wear impermeable protective gloves, Wear goggles or protective glasses with side shields. Do not ingest.

**CLOSE CONTAINER AFTER EACH USE.
KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists..

SKIN: Wash affected areas with soap and water. Consult a physician if irritation persists.

INGESTION: Product hardens when wetted and if ingested may result in an obstruction.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Mar-Gon Floor Leveler and Crack Filler
4 LB. 4/Case01217
25 LB. 1/Case01227

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.