

UGL® Powdered Tile Grout

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

UGL Powdered Tile Grout repairs and restores bathroom, kitchen, and wall tile to its original beauty. Fills cracks around sink and bathtub wall tile and ceramic fixtures. Seals seams between floor and wall tile.

- Repair and restore tile to its original beauty
- Fill cracks and breaks around bathtubs, sinks and towel racks
- Seal seams between floor/wall tile
- Water resistant
- Dries hard and white

BASIC USES

It can be used to grout ceramic and mosaic tile, around bathtubs, sinks and towel rack, and seams between floor and wall tile

LIMITATIONS

Mix only enough for immediate use, because UGL Powdered Tile Grout sets in 30 minutes. Cannot be reworked once it has set.

TECHNICAL DATA

COMPOSITION:

Powder, mix with water

SHEEN:

N/A

% WEIGHT SOLIDS:

100%

% VOLUME SOLIDS:

100%

DENSITY (LBS./US GAL.):

20.6

VISCOSITY:

Powder

pH:

N/A

COLORS:

White

SET TIME:

- 12 hours
- Subject to water: 24 hours

Note: Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US LB.):

- Ceramic tile: 12-15 sq. ft./lb.
- Mosaic tile: 4-6 sq. ft./lb.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

Indefinite in sealed container

FREEZE/THAW:

N/A

CONTAINER SIZES:

Four pound (US) plastic pail

VOC

N/A g/L

TINTING

N/A

SURFACE PREPARATION

Surface must be clean. Remove soap film by wiping with denatured alcohol. Remove mildew with a bleach and water solution.

New Work: Mastic adhesive must be fully cured. Surface must be clean and firm.

Old Work: Remove all old and loose grout. Clean surface thoroughly. Replace damaged tile.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

MIXING

Mix Powdered Tile Grout at a ratio of 2 1/2 cups Tile Grout to 1 cup clean water in a clean container. Slowly add water, stirring constantly until a heavy, creamy consistency is obtained. Do not mix more than can be used in 45 minutes.

APPLICATION

Dampen entire surface using a clean, wet sponge. This will ensure proper cure of Tile Grout. To avoid skin irritation, wear rubber gloves. Force Tile Grout into crack or joint with a plastic putty knife. Smooth the area while damp and allow 30 minutes for the Tile Grout to harden. Remove excess Grout by wiping with a clean, damp cloth or sponge. Allow to cure 12 hours, polish tile with a clean, dry cloth.

Clean tools with water immediately after use.



SET TIME:
12 Hour



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application



SPREAD RATE:
4-15 Sq. Ft./Lb.

CAUTION

Contains Portland Cement. Avoid contact with eyes. In case of eye contact, flood eyes repeatedly with water and call a physician.

KEEP OUT OF REACH OF CHILDREN

FIRST AID

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists..

SKIN: Wash affected areas with soap and water. Consult a physician if irritation persists.

INGESTION: Product hardens when wetted and if ingested may result in an obstruction.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Powdered Tile Grout
4 LB. 4/Case01617

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.